



2019

Non Fail-Safe Product Range

Small Devices, Big Impact.

CESIM is the Belimo method to innovate building technology with sensors, valves, and actuators. As a member of the UN Global Compact, Belimo is an active stakeholder contributing to the Sustainable Development Goals (SDG) directly. By incorporating the UN Global Compact principles into strategies, policies, and procedures, Belimo is not only upholding their basic responsibilities to people and the planet, but also setting the stage for long-term success of our industry.

CESIM ensures that the “small” Belimo devices have a big impact on Comfort, Energy Efficiency, Safety, Installation, and Maintenance.



Find out more
www.belimo.us/cesim



PMB, GMB(X), and AMB Non Fail-Safe Damper Actuator Product Range

PMB, GMB(X), and AMB Non Fail-Safe Damper Actuator Product Range		Power Supply			Power Consumption		Running Time	Housing Type	Drive Type	Custom Options			Control Input				Control Input MFT			Position Feedback			Bulk Pack				
		24 VAC ± 20%, 50/60 Hz VDC ±10%	24 to 240 VAC +10%/- 20%, 50/60 Hz 24 to 125 VDC ± 10%	100 VAC to 240 VAC ±10%	VA Rating	Wattage Running (Holding)	Motor Drive (Default)	NEMA 1 or 2	NEMA 4/4X, (with Heater)	Rotary "M", Linear "L", Multi-turn "U"	Select Mechanical Coupler	Select Electrical Connection	On/Off	Floating Point	2-10 VDC or 4-20 mA (w/500 Ω Resistor)	Honeywell Series 90, 0-135 Ω	BACnet: MS/TP or Modbus RTU (1) BACnet/IP or Modbus TCP (2)	0-20v Phasecut	On/Off	Floating Point	Start and Span adj., Start 0.5 to 30 VDC Span 2.5 to 32 VDC	PWM adj., 0.02 to 50.0 Seconds	2-10 VDC (Default) Adjustable with MFT	Digital (1), Resistive Feedback	1 SPDT, 3A (0.5A Inductive) @ 250V	Optional Accessories:Aux. Switch (S1A, S2A), Potentiometer (PxxA GR)	Quantity of Actuators in Bulk Pack
PMB Series 1400 in-lbs [160 Nm]	PMBUP-3-T	●			23	18	35		4X(H)	M			●	●													
	PMBUP-MFT-T	●			19	19 (3.5)	35		4X(H)	M			●	●	●		1		●	●			●				
GMB Series 360 in-lbs [40 Nm] Approx. 90 sq.ft.	GMB24-3	●			6	4.0 (2.0)	150	2		M			●	●												●	
	GMB24-3-T N4	●			6	4.0 (2.0)	150		4X	M			●	●												●	
	GMB24-3-T N4H	●			6	4.0 (2.0)	150		4X(H)	M			●	●												●	
	GMB24-SR	●			6.5	4.5 (2.0)	150	2		M					●								●			●	
	GMB24-SR-T N4	●			6.5	4.5 (2.0)	150		4X	M					●								●			●	
	GMB24-SR-T N4H	●			6.5	4.5 (2.0)	150		4X(H)	M					●								●			●	
	GMB24-IP	●			8	5.5 (5)	150	1		M							2						●	1		●	
	GM24A-MOD	●			7	4 (1.6)	150			M							1							1		●	
	GMB24-MFT	●			7	4.0 (1.5)	150	2		M									●	●	●	●	●			●	
GMX Series 360 in-lbs [40 Nm] Approx. 90 sq.ft.	Customizable *	GMX24-3	●		6	4.0 (2.0)	150	2		M	●	●	●	●												●	
		GMX24-3-T N4	●			6	4.0 (2.0)	150		4X	M	●	●	●	●											●	
		GMX24-3-T N4H	●			6	4.0 (2.0)	150		4X(H)	M	●	●	●	●											●	
		GMX24-SR	●			6.5	4.5 (2.0)	150	2		M	●	●			●								●		●	
		GMX24-SR-T N4	●			6.5	4.5 (2.0)	150		4X	M	●	●			●								●		●	
		GMX24-SR-T N4H	●			6.5	4.5 (2.0)	150		4X(H)	M	●	●			●								●		●	
		GMX24-PC	●			7	4.0 (1.5)	150	2		M	●	●					●						●		●	
		GMX120-3		●		7	4.0 (2.0)	150	2		M	●	●	●	●											●	
		GMX24-MFT	●			7	4.0 (1.5)	75-300 (150)	2		M	●	●							●	●	●	●			●	
		GMX24-MFT-T	●			7	4.0 (1.5)	75-300 (150)	1		M	●	●							●	●	●	●			●	
		GMX24-MFT N4	●			7	4.0 (1.5)	75-300 (150)		4X	M	●	●							●	●	●	●			●	
GMX24-MFT N4H	●			7	4.0 (1.5)	75-300 (150)		4X(H)	M	●	●							●	●	●	●			●			
AMB Series 180 in-lbs [20 Nm] Approx. 45 sq.ft.		AMB24-3	●			5.5	2.5 (0.5)	95	2		M			●	●											●	
		AMB24-3-T N4	●			5.5	2.5 (0.5)	95		4X	M			●	●											●	
		AMB24-3-T N4H	●			5.5	2.5 (0.5)	95		4X(H)	M			●	●											●	
		AMB24-3-S	●			5.5	2.5 (0.5)	95	2		M			●	●									●		●	
		AMB24-SR	●			5	2.5 (0.4)	95	2		M					●							●			●	
		AMB24-SR-T	●			5	2.5 (0.4)	95	1		M					●							●			●	
		AMB24-SR-T N4	●			5	2.5 (0.4)	95		4X	M					●							●			●	
		AMB24-SR-T N4H	●			5	2.5 (0.4)	95		4X(H)	M					●							●			●	
		AMB24-IP	●			8	6 (3)	150	1		M							2					●	1		●	
		SM24A-MOD	●			6	3.5 (1.4)	150			M							1						1		●	
		AMB24-MFT	●			6	3.5 (1.3)	150	2		M									●	●	●	●			●	
		AMCB24-MFT	●			6	3.5 (1.3)	35	2		M									●	●	●	●			●	
		AMB120-3		●		7	3.0 (0.6)	95	2		M			●	●											●	

Visit www.belimo.us for detailed product specifications and downloadable data sheets.
*See pages 4-13 to 4-16 of the Product Guide and Price List for customization options.

AMX, AHB(X),
AMQB(X), AHQB(X)
Non Fail-Safe
Damper Actuator
Product Range



AMX Series 180 in-lbs [20 Nm] Approx. 45 sq.ft.	Customizable*	AMX24-3	●		5.5	2.5 (0.5)	95	2		M	●	●	●	●												●		
		AMX24-3-T	●		5.5	2.5 (0.5)	95	1		M	●	●	●	●												●		
		AMX24-3-T N4	●		5.5	2.5 (0.5)	95		4X	M	●	●	●	●												●		
		AMX24-3-T N4H	●		5.5	2.5 (0.5)	95		4X (H)	M	●	●	●	●												●		
		AMX24-SR	●		5	2.5 (0.4)	95	2		M	●	●			●										●		●	
		AMX24-SR-T	●		5	2.5 (0.4)	95	1		M	●	●			●										●		●	
		AMX24-SR-T N4	●		5	2.5 (0.4)	95		4X	M	●	●			●										●		●	
		AMX24-SR-T N4H	●		5	2.5 (0.4)	95		4X (H)	M	●	●			●										●		●	
		AMX24-PC	●		5.5	3.5 (1.3)	90	2		M	●	●						●							●		●	
		AMX120-3		●	7	3.0 (0.6)	95	2		M	●	●	●	●												●		
		AMX120-SR		●	7.5	4.0 (1.0)	95	2		M	●	●			●										●		●	
		AMX24-MFT	●		6	3.5 (1.3)	90-300 (150)	2		M	●	●							●	●	●	●	●			●		
		AMX24-MFT N4	●		6	3.5 (1.3)	90-300 (150)		4X	M	●	●								●	●	●	●	●			●	
		AMX24-MFT N4H	●		6	3.5 (1.3)	90-300 (150)		4X (H)	M	●	●									●	●	●	●	●			●
AMCX24-MFT	●		6	3.5 (1.3)	35-120 (35)	2		M	●	●									●	●	●	●	●			●		
AMX24-MFT95	●		6	3.5 (1.3)	75-150 (150)	2		M	●	●			●											●		●		
AHB Series 101 lbf [450 N Force] 4" or 8" stroke		AHB24-3-100	●		4.5	2.0 (0.5)	150	2		L, 4"			●	●														
		AHB24-3-200	●		4.5	2.0 (0.5)	150	2		L, 8"			●	●														
		AHB24-SR-100	●		4.5	2.5 (0.5)	150	2		L, 4"					●										●			
		AHB24-SR-200	●		4.5	2.5 (0.5)	150	2		L, 8"					●											●		
AHX Series 101 lbf [450 N Force] 4", 8", 12" stroke	Customizable*	AHX24-3-100	●		4.5	2.0 (0.5)	150-450 (150)	2		L, 4"		●	●	●														
		AHX24-3-200	●		4.5	2.0 (0.5)	150-450 (150)	2		L, 8"		●	●	●														
		AHX24-3-300	●		4.5	2.0 (0.5)	150-450 (150)	2		L, 12"		●	●	●														
		AHX120-3-100		●	4.5	2.5 (0.5)	150-450 (150)	2		L, 4"		●	●	●														
		AHX120-3-200		●	4.5	2.5 (0.5)	150-450 (150)	2		L, 8"		●	●	●														
		AHX120-3-300		●	4.5	2.5 (0.5)	150-450 (150)	2		L, 12"		●	●	●														
		AHX24-SR-100	●		4.5	2.5 (0.5)	150-450 (150)	2		L, 4"		●			●										●			
		AHX24-SR-200	●		4.5	2.5 (0.5)	150-450 (150)	2		L, 8"		●			●											●		
		AHX24-MFT-100	●		6	3.5 (1.3)	150-450 (150)	2		L, 4"		●									●	●	●	●	●			
		AHX24-MFT-200	●		6	3.5 (1.3)	150-450 (150)	2		L, 8"		●									●	●	●	●	●			
AHX24-MFT-300	●		6	3.5 (1.3)	150-450 (150)	2		L, 12"		●									●	●	●	●	●					
AMQB(X) 140 in-lbs [16 Nm]		AMQB24-1	●		26	15 (1.5)	7	2		M			●												●			
		AMQB24-MFT	●		26	15 (1.5)	7	2		M										●		●		●		●		
AHQB(X) 44 lbf [200 N Force]	C*	AMQX24-MFT	●		26	15 (1.5)	7-15 (7)	2		M	●	●								●		●		●		●		
	C*	AHQB24-1-100	●		23	13 (1.5)	7	2		L, 4"			●								●		●		●			
		AHQB24-MFT-100	●		23	13 (1.5)	7	2		L, 4"											●		●		●			
	C*	AHQX24-MFT-100	●		23	13 (1.5)	7-20 (7)	2		L, 4"	●									●		●		●				

800-543-9038 USA

866-805-7089 CANADA

203-791-8396 LATIN AMERICA/CARIBBEAN

NMB(X), NMQB(X) Non Fail-Safe Damper Actuator Product Range



V10001 - 01/19 - Subject to change. © Belimo Aircontrols (USA), Inc.

NMB(X), NMQB(X) Non Fail-Safe Damper Actuator Product Range			Power Supply		Power Consumption		Running Time	Housing Type		Drive Type	Custom Options		Control Input				Control Input MFT		Position Feedback			Bulk Pack									
			24 VAC ± 20%, 50/60 Hz VDC ±10%	24 to 240 VAC +10%/- 20%, 50/60 Hz 24 to 125 VDC ± 10%	100 VAC to 240 VAC ±10%	VA Rating	Wattage Running (Holding)		Motor Drive (Default)	NEMA 1 or 2	NEMA 4/4X, (with Heater)	Rotary "M", Linear "L", Multi-turn "U"	Select Mechanical Coupler	Select Electrical Connection	On/Off	Floating Point	2-10 VDC or 4-20 mA (w/500 Ω Resistor)	Honeywell Series 90, 0-135 Ω	BACnet: MS/TP or Modbus RTU (1)	BACnet/IP or Modbus TCP (2)	0-20v Phasecut	On/Off	Floating Point	Start and Span adj., Start 0.5 to 30 VDC Span 2.5 to 32 VDC	PWM adj., 0.02 to 50.0 Seconds	2-10 VDC (Default) Adjustable with MFT	Digital (1), Resistive Feedback	1 SPDT, 3A (0.5A Inductive) @ 250V	Optional Accessories:Aux. Switch (S1A, S2A), Potentiometer (PxxA GR)	Quantity of Actuators in Bulk Pack	
NMB Series 90 in-lbs [10 Nm] Approx. 22 sq. ft.		NMB24-3	●			4	2.0 (0.2)	95	2		M			●	●														●		
		NMB24-3-T N4	●			4	2.0 (0.2)	95		4X	M			●	●														●		
		NMB24-3-T N4H	●			4	2.0 (0.2)	95		4X(H)	M			●	●														●		
		NMCB24-3	●			4	2.5 (0.2)	45	2		M			●	●														●		
		NMB24-SR	●			5	2.5 (0.4)	95	2		M					●										●			●		
		NMB24-SR-T	●			5	2.5 (0.4)	95	1		M					●										●			●		
		NMB24-SR-T N4	●			5	2.5 (0.4)	95		4X	M					●										●			●		
		NMB24-SR-T N4H	●			5	2.5 (0.4)	95		4X(H)	M					●										●			●		
		NMCB24-SR	●			5	2.5 (0.4)	45	2		M					●										●			●		
		NMB24-IP	●			6	4 (3)	150	1		M							2								●	1		●		
		NM24A-MOD	●			6	3.5 (1.4)	150			M						1										1			●	
		NMB24-MFT	●			6	3.5 (1.3)	150	2		M	●	●									●	●	●	●	●				●	
NMX Series 90 in-lbs [10 Nm] Approx. 22 sq. ft.	Customizable*	NMX24-3	●			4	2.0 (0.2)	95	2		M	●	●	●	●														●		
		NMX24-3-T	●			4	2.0 (0.2)	95	1		M	●	●	●	●														●		
		NMX24-3-T N4	●			4	2.0 (0.2)	95		4X	M	●	●	●	●														●		
		NMX24-3-T N4H	●			4	2.0 (0.2)	95		4X(H)	M	●	●	●	●														●		
		NMX24-SR	●			5	2.5 (0.4)	95	2		M	●	●			●										●			●		
		NMX24-SR-T	●			5	2.5 (0.4)	95	1		M	●	●			●										●			●		
		NMX24-SR-T N4	●			5	2.5 (0.4)	95		4X	M	●	●			●										●			●		
		NMX24-SR-T N4H	●			5	2.5 (0.4)	95		4X(H)	M	●	●			●										●			●		
		NMX120-3		●		5.5	2.5 (0.6)	150	2		M	●	●	●	●														●		
		NMX120-SR		●		6.5	3.5 (1.0)	150	2		M	●	●			●													●		
		NMX24-MFT	●			6	3.5 (1.3)	45-150 (150)	2		M	●	●									●	●	●	●	●			●		
		NMX24-MFT N4	●			6	3.5 (1.3)	45-150 (150)		4X	M	●	●									●	●	●	●	●			●		
		NMX24-MFT N4H	●			6	3.5 (1.3)	45-150 (150)		4X(H)	M	●	●									●	●	●	●	●			●		
		NMX24-MFT95	●			6	3.5 (1.3)	45-150 (150)	2		M	●	●			●										●			●		
NMCX24-MFT	●			5	3.0 (0.6)	20-75 (45)	2		M	●	●									●	●	●	●	●			●				
NMQB(X) 70 in-lbs [8 Nm]	C	NMQB24-1	●			20	13 (1.5)	4	2		M			●														●			
		NMQB24-MFT	●			20	13 (1.5)	4	2		M										●		●		●			●			
		NMQX24-MFT	●			23	13 (1.5)	4-20 (4)	2		M	●	●									●		●		●			●		

Visit www.belimo.us for detailed product specifications and downloadable data sheets.
*See pages 4-13 to 4-16 of the Product Guide and Price List for customization options.

LMB(X), LHB Non Fail-Safe Damper Actuator Product Range



Power Supply		Power Consumption		Running Time	Housing Type	Drive Type	Custom Options	Control Input				Control Input MFT		Position Feedback		Bulk Pack								
24 VAC ± 20%, 50/60 Hz VDC ±10%	24 to 240 VAC +10%/- 20%, 50/60 Hz 24 to 125 VDC ± 10%	100 VAC to 240 VAC ±10%	VA Rating	Wattage Running (Holding)	Motor Drive (Default)	NEMA 1 or 2	NEMA 4/4X, (with Heater)	Rotary "M", Linear "L", Multi-turn "U"	Select Mechanical Coupler	Select Electrical Connection	On/Off	Floating Point	2-10 VDC or 4-20 mA (w/500 Ω Resistor)	Honeywell Series 90, 0-135 Ω	BACnet: MS/TP or Modbus RTU (1) BACnet/IP or Modbus TCP (2)	0-20v Phasecut	On/Off	Floating Point	Start and Span adj., Start 0.5 to 30 VDC Span 2.5 to 32 VDC	PWM adj., 0.02 to 50.0 Seconds	2-10 VDC (Default) Adjustable with MFT	Digital (1), Resistive Feedback	1 SPDT, 3A (0.5A Inductive) @ 250V Optional Accessories: Aux- Switch (S1A, S2A), Potentiometer (PxxA GR)	Quantity of Actuators in Bulk Pack
●			2	1.5 (0.2)	95	2		M			●	●											●	
●			2.5	1.5 (0.2)	35	2		M			●	●											●	
●			2	1.5 (0.2)	95	2		M			●	●											●	24
●			2	1.5 (0.2)	95	2		M			●	●										●	●	
●			2	1.5 (0.2)	95	1		M			●	●											●	
●			2.5	1.5 (0.2)	35	1		M			●	●											●	
●			2	1.5 (0.2)	95	1		M			●	●											●	36
●			2	1.5 (0.2)	95	1		M			●	●									5kΩ	●	●	
●			2	1.5 (0.2)	95	1		M			●	●									5kΩ	●	●	36
●		●	2	1.5 (0.2)	95	1		M			●	●									10kΩ	●	●	
●			4	2.0 (0.5)	150	2		M			●	●											●	
●			3	1.5 (0.4)	95	2		M					●								●		●	
●			3	1.5 (0.4)	35	2		M					●								●		●	
●			3	1.5 (0.4)	95	2		M					●								●		●	24
●			3	1.5 (0.4)	95	1		M					●								●		●	
●			3	1.5 (0.4)	35	1		M					●								●		●	
●			3	1.5 (0.4)	95	1		M					●								●		●	36
●			4.5	3 (2)	150	1		M							2						●	1	●	
●			5	2.5 (1.3)	150	2		M						1								1	●	
●			5	2.5 (1.2)	150	2		M									●	●	●	●	●		●	
●			2	1.5 (0.2)	95	1		M															●	
●			2	1.5 (0.2)	95	1		M														10kΩ	●	
●			2	1.5 (0.2)	95	2		M	●	●	●	●											●	
●			2	1.5 (0.2)	95	1		M	●	●	●	●											●	
●			3	1.5 (0.4)	95	2		M	●	●			●										●	
●			3	1.5 (0.4)	95	1		M	●	●			●										●	
		●	4	2.0 (0.5)	150	2		M	●	●	●	●											●	
		●	4.5	2.5 (1.0)	150	2		M	●	●			●									●	●	
●			5	2.5 (1.2)	35-200 (150)	2		M	●	●							●	●	●	●	●		●	
●			5	2.5 (1.2)	35-150 (150)	2		M	●	●			●									●	●	
●			3	1.5 (0.5)	150	2		L, 4"			●	●												
●			3	1.5 (0.5)	150	2		L, 4"			●	●												
●			3	1.5 (0.5)	300	2		L, 8"			●	●												
●			3	1.5 (0.5)	150	2		L, 4"					●									●		
●			3	1.5 (0.5)	300	2		L, 8"					●									●		

Visit www.belimo.us for detailed product specifications and downloadable data sheets.
*See pages 4-13 to 4-16 of the Product Guide and Price List for customization options.

LHX, LMQB(X), LHQB(X), LUB(X), and CMB Non Fail-Safe Damper Actuator Product Range



Power Supply			Power Consumption		Running Time	Housing Type	Drive Type	Custom Options	Control Input				Control Input MFT		Position Feedback		Bulk Pack									
24 VAC ± 20%, 50/60 Hz VDC ±10%	24 to 240 VAC +10%/- 20%, 50/60 Hz	24 to 125 VDC ± 10%	100 VAC to 240 VAC ±10%	VA Rating	Wattage Running (Holding)	Motor Drive (Default)	NEMA 1 or 2	NEMA 4/4X, (with Heater)	Rotary "M", Linear "L", Multi-turn "U"	Select Mechanical Coupler	Select Electrical Connection	On/Off	Floating Point	2-10 VDC or 4-20 mA (w/500 Ω Resistor)	Honeywell Series 90, 0-135 Ω	BACnet: MS/TP or Modbus RTU (1) BACnet/IP or Modbus TCP (2)	0-20v Phasecut	On/Off	Floating Point	Start and Span adj., Start 0.5 to 30 VDC Span 2.5 to 32 VDC	PWM adj., 0.02 to 50.0 Seconds	2-10 VDC (Default) Adjustable with MFT	Digital (1), Resistive Feedback	1 SPDT, 3A (0.5A Inductive) @ 250V	Optional Accessories:Aux. Switch (S1A, S2A), Potentiometer (PxxA GR)	Quantity of Actuators in Bulk Pack
●			3	1.5 (0.5)	70-270 (150)	2	L, 4"		●	●	●															
●			3	1.5 (0.5)	140-540 (300)	2	L, 8"		●	●	●															
●			3	1.5 (0.5)	200-810 (450)	2	L, 12"		●	●	●															
		●	2.5	1.5 (0.5)	70-270 (150)	2	L, 4"		●	●	●															
		●	2.5	1.5 (0.5)	140-540 (300)	2	L, 8"		●	●	●															
		●	2.5	1.5 (0.5)	200-810 (450)	2	L, 12"		●	●	●															
●			3	1.5 (0.5)	70-270 (150)	2	L, 4"		●				●										●			
●			3	1.5 (0.5)	140-540 (300)	2	L, 8"		●				●										●			
●			5	2.5 (1.2)	70-270 (150)	2	L, 4"		●									●	●	●	●	●				
●			5	2.5 (1.2)	140-540 (300)	2	L, 8"		●									●	●	●	●	●				
●			5	2.5 (1.2)	200-810 (450)	2	L, 12"		●									●	●	●	●	●				
●			20	13 (1.5)	2.5	2	M				●														●	
●			20	13 (1.5)	2.5	2	M											●		●		●			●	
●			20	13 (1.5)	2.5-10 (2.5)	2	M	●	●									●		●		●			●	
●			23	13 (1.5)	3.5	2	L, 4"				●															
●			23	13 (1.5)	3.5	2	L, 4"											●		●		●				
●			23	13 (1.5)	3.5-15 (3.5)	2	L, 4"		●									●		●		●				
●			2.5	1.0 (0.5)	600	2	U, 360°				●	●														
●			3	3.0 (0.5)	600	2	U, 360°							●								●				
●			2.5	1.0 (0.5)	150	2	U, 360°	●	●	●	●															
●			3	1.5 (0.5)	150	2	U, 360°	●	●				●									●				
●			5	2.5 (1.2)	75-150 (150)	2	U, 360°	●	●									●	●	●	●	●				
●			1.5	1.0 (0.2)	35	2	M				●	●														
●			1.5	1.0 (0.2)	35	2	M				●	●														20
		●	3.5	1.5 (1.0)	35	2	M				●	●														
●			1.5	1.0 (0.2)	35	1	M				●	●														
●			1.5	1.0 (0.2)	35	1	M				●	●														20
●			2.5	1.5 (0.5)	35	2	M							●												
●			2.5	1.5 (0.5)	35	2	M							●												
●			1	0.5 (0.2)	380	1	L, 4"				●	●														20

Visit www.belimo.us for detailed product specifications and downloadable data sheets.
*See pages 4-13 to 4-16 of the Product Guide and Price List for customization options.

Belimo Americas Platinum Distributors

USA

ACR Supply Company Inc.
4040 S. Alston Avenue
Durham, NC 27713
Phone: 919-765-8081
With branches in NC

Aireco Supply
9120 Washington Boulevard
Savage, MD 20763-0414
Phone: 301-953-8800
With branches in MD, VA

Amcon Controls, Inc.
11906 Warfield Street
San Antonio, TX 78216
Phone: 210-349-6161
With branches in Houston, TX
and Mandeville, LA

Relevant Solutions
(formerly Applied Automation)
3186 South Washington Street, #230
Salt Lake City, UT 84115
Phone: 801-486-6454
With branches in CA, CO, TX

Boston Aircontrols, Inc.
8 Blanchard Road
Burlington, MA 01803
Phone: 781-272-5800

Charles D. Jones Co.
445 Bryant Street, Unit #1
Denver, CO 80204-4800
Phone: 800-777-0910
With branches in CO, MO, KS

Cochrane Supply and Engineering, Inc.
30303 Stephenson Highway
Madison Heights, MI 48071-1633
Phone: 800-482-4894
With branches in MI, OH and KY

Columbus Temperature Control
1053 E. 5th Avenue
Columbus, OH 43201
Phone: 800-837-1837

Controlco
3451 Vincent Road
Pleasant Hill, CA 94523
Phone: 916-927-5599
With branches in CA, NV, TN

Control Depot
9304 G Court
Omaha, NE 68127
Phone: 866-809-7408
With a branch in Lincoln, NE

Control Products
9101 Jameel, Suite 130
Houston, TX 77447
Phone: 713-849-7200
With a branch in San Antonio, TX

Control Stop
1000 N Pine Street, Suite 6
Spartanburg, SC 29303
Phone: (864) 586-3818
With a branch in NC

Engineered Control Systems
5627 NW 74th Avenue
Miami, FL 33166
Phone: 305-885-8804
With branches in FL

G & O Thermal Supply
5435 N. Northwest Highway
Chicago, IL 60630
Phone: 773-763-1300
With branches in IL, IN and WI

Industrial Controls Distributors, LLC
(formerly Climatic Control)
1245 W. Canal Street
Milwaukee, WI 53233
Phone: 414-259-9070
With branches in WI

Industrial Controls Distributors, LLC
17 Christopher Way
Eatontown, NJ 07724
Phone: 800-543-8200
With branches in GA, KY, IN, MA, ME,
NC, NY, OH, PA, TN

Interstate HVAC Controls
30 Vineland Street
Brighton, MA 02135
Phone: 617-782-9000

Jackson Controls
1708 E. 10th Street
Indianapolis, IN 46201
Phone: 317-231-2200

M & M Controls
9E West Aylesbury Road
Timonium, MD 21093
Phone: 410-252-1221
With branches in VA

Meier Supply
275 Broome Corporate Pwky
Conklin, NY 13748
Phone: 607-797-7700
With branches in NY, PA

Minvalco, Inc.
3340 Gorham Avenue
Minneapolis, MN 55426-4267
Phone: 952-920-0131
With branches in MN

Relevant Solutions
9750 West Sam Houston Pwky North
Suite 190
Houston, TX 77064
Phone: 281-295-8850

RSD / Refrigeration Supplies Distributor
26021 Atlantic Ocean Drive
Lake Forest, CA 92630
Phone: 949-380-7878
With branches in CA, NV, OR, AK, AZ,
ID, UT, WA, MT

Saint Louis Boiler Supply, Co.
617 Hanley Industrial Court
St. Louis, MO 63144
Phone: 314-962-9242

South Side Control Supply, Co.
488 N. Milwaukee Avenue
Chicago, IL 60610-3923
Phone: 312-226-4900
With branches in IL, IN

Stromquist and Company
4620 Atlanta Road
Smyrna, GA 30080
Phone: 404-794-3440
With a branch in Orlando, FL

Temperature Control Systems
10315 Brockwood Road
Dallas, TX 75238
Phone: 214-343-1444
With branches in OK, TX

T.F. Campbell Company
1203 Edgebrook Avenue
Pittsburgh, PA 15226
Phone: 412-881-8006

Tower Equipment Co., Inc.
1320 West Broad Street
Stratford, CT 06615
Phone: 800-346-4647

Twinco Supply Corporation
55 Craven Street
Huntington Station, NY 11746-2143
Phone: 800-794-3188
With branches in NY

Canada

For a complete list of distributors
in Canada, please visit our
website: www.belimo.ca
or call toll free: 866-805-7089

Brazil

For a complete list of distributors
in Brazil, please visit our
website: www.belimo.com.br
or call: 55 11 3643-5656

Latin America & the Caribbean

For a complete list of distributors
in Latin America and the Caribbean,
please visit our website: www.belimo.us
or call: 203-791-8396



Belimo Americas

USA, Latin America, and the Caribbean: www.belimo.us

Canada: www.belimo.ca

Brazil: www.belimo.com.br

Belimo Worldwide: www.belimo.com

