Humidistats and Thermostats


HP970 Pneumatic Humidistat	2
HP972 Pneumatic Humidistat	3
Humidistat Cover Assemblies	4
Humidistat Accessories	4
Replacement Parts	4
LP907 Airstream Insertion Pneumatic Thermostat	5
LP916 Pneumatic Thermostat	6
TP9600 Pneumatic Thermostat	8
TP970 Pneumatic Thermostat	9
TP971 Pneumatic Day/Night Thermostat	11
TP972 Pneumatic Heating/Cooling Thermostat	13
TP973 Pneumatic Thermostat	15
TP975 Pneumatic Diffuser Thermostat	17
Pneumatic Thermostat Accessories	18
Pneumatic Thermostat Replacement Parts	22
TP9600 Series Standard Covers	23
TP970 Series Standard Covers	24

Humidistats

HP970 Pneumatic Humidistat



HP970 Typical Piping



Application: Humidity

Dimensions, Approximate: 3 1/4 in. high x 2 in. wide x 1 5/8 in. deep

(83 mm high x 51 mm wide x 41 mm deep) Airflow Usage: 0.011 scfm (5.2 mL/s)

Maximum Operating Temperature: 45 F to 125 F (7 C to 52 C)
Maximum Storage Temperature: -30 to +150 F (-34 to +66 C)

Maximum Operating Pressure: 25 psi (170 kPa)

Accessories:

14002362-001 Duct Sampling Chamber

14002374-004 Restrictor Block Assembly, .005 in., For TP970A-D; TP971A-E except C; TP972A; TP973A-B; TP9600 family; HP970A-B; and HP972B

Two-pipe, single setpoint, pneumatic humidistat used to provide proportional control of pneumatic valves on humidification or dehumidification systems.

- Durable HP970 series humidistat.
- Pilot operated for high capacity.
 Direct Acting (DA) and Reverse Acting (RA) models are available.
- Vertical or horizontal mounting.
- Backplate has molded air connections; no separate fittings needed.
- Variety of cover finishes and display styles available.

14002430-001 Thermostat Guard

- 14003192-001 Wallplate adapter kit. Adapts HP970 or TP970 series stats to HP900 and TP900 flush mounted and TP910 series flush or surface mounted installations
- **14004406-124** Humidistat Cover assembly Satin Chrome with setpoint display and Honeywell logo for vertical mounting, scale range 15 to 75% RH

305965 1-1/2 in. diameter, 1/8 NPT center stem back mount Pressure Indicating gauge (0 to 30 psi scale) with +/- 4% accuracy

AK3863 Honeywell Thermostat Tool Kit, TP970/TP900

CCT729A Gauge Adapter for Calibration. Add 305965 0 to 30 psi gauge for Complete Tool.

CCT735A Thermostat Calibration Tool includes Allen wrench for cover installation.

For additional covers, see Humidistat Cover Assemblies

Replacement Parts:

14001865-001 Filter Cartridge Assembly 14002053-001 Back Plate Assembly

14002374-004 Restrictor Block Assembly, 0.005 in., For TP970A-D; TP971A-E except C; TP972A; TP973A-B; TP9600 family; HP970A-B; and HP972B

14002573-001 Modernization Kit to convert all 1 & 2 pipe Honeywell & competitive pneumatic stats to TP970, TP971A, TP972, TP973, TP974, TP9600 family; HP970, HP971 and HP972


Product Number	Action Number of Pipes		Scale Range (% RH) Throttling Range (%		Setpoint	Comments	
HP970A1009	Direct Acting	2	15 to 75% RH	3 to 15% RH	Single	Order Cover Separately	
HP970B1007	Reverse Acting	2	15 to 75% RH	3 to 15% RH	Single	Order Cover Separately	
HP970B1015	Reverse Acting	2	65 to 95% RH	3 to 15% RH	Single	Order Cover Separately	

Humidistats

HP972 Pneumatic Humidistat



Typical Two-Pipe HP972B Hook-up



Application: Humidity

Dimensions, Approximate: 3 1/4 in. high x 2 in. wide x 1 5/8 in. deep

(83 mm high x 51 mm wide x 41 mm deep) Airflow Usage: 0.011 scfm (5.2 mL/s)

Maximum Operating Temperature: 45 F to 125 F (7 C to 52 C)
Maximum Storage Temperature: -30 to +150 F (-34 to +66 C)

Maximum Operating Pressure: 25 psi (170 kPa)


Accessories:

- 14002430-001 Thermostat Guard
- 14002362-001 Duct Sampling Chamber
- 14004406-124 Humidistat Cover assembly Satin Chrome with setpoint display and Honeywell logo for vertical mounting, scale range 15 to
- 14003192-001 Wallplate adapter kit. Adapts HP970 or TP970 series stats to HP900 and TP900 flush mounted and TP910 series flush or surface mounted installations
- 305965 1-1/2 in. diameter, 1/8 NPT center stem back mount Pressure Indicating gauge (0 to 30 psi scale) with +/- 4% accuracy

A proportioning pneumatic humidistat used on one- or two-pipe installations for controlling actuators on valves and dampers in air conditioning systems for humidification or dehumidification control.

- Durable HP970 series humidistat.
- Snap-on mounting to backplate. Vertical or horizontal mounting.
- Backplate has molded air connections; no separate fittings needed.
- Variety of cover finishes and display styles available.
- Wide throttling range.

Typical One-pipe HP972B Hook-up



AK3863 Honeywell Thermostat Tool Kit, TP970/TP900

CCT729A Gauge Adapter for Calibration. Add 305965 0 to 30 psi gauge for Complete Tool.

CCT735A Thermostat Calibration Tool includes Allen wrench for cover installation.

For additional covers, see Humidistat Cover Assemblies

Replacement Parts:

14001865-001 Filter Cartridge Assembly

14002496-003 Nylon element assembly, with Spring

14002573-001 Modernization Kit to convert all 1 & 2 pipe Honeywell & competitive pneumatic stats to TP970, TP971A, TP972, TP973, TP974, TP9600 family; HP970, HP971 and HP972

14002374-004 Restrictor Block Assembly, .005 in., For TP970A-D; TP971A-E except C; TP972A; TP973A-B; TP9600 family; HP970A-B; and HP972B

14002053-001 Back Plate Assembly

Product Number	Action	Number of Pipes	Scale Range (% RH)	Throttling Range (% RH)	Setpoint	Comments
HP972B1005	Reverse Acting	1 or 2	15 to 75% RH	7 to 35% RH	Single	Order Cover Separately

Honeywell 70-6925

3

Humidistats

Humidistat Cover Assemblies

Product Number	Scale Range (% RH)	Description	Used With
14004406-124	15 to 75% RH	Humidistat Cover assembly Satin Chrome with setpoint display and Honeywell logo for vertical mounting, scale range 15 to 75% RH	HP970; HP972
14004406-224	15 to 75% RH	Humidistat Cover assembly Satin Chrome with setpoint display and Honeywell logo for horizontal mounting. Scale Range 15 to 75% RH	HP970; HP972
14004406-300	_	Humidistat Cover assembly Satin Chrome with no setpoint display and Honeywell logo for vertical mounting	HP970; HP972
14004406-400	_	Humidistat Cover assembly Satin Chrome with no setpoint display and Honeywell logo for horizontal mounting	HP970; HP972
14004406-800	_	Humidistat Cover assembly Satin Chrome with no setpoint display and no logo for vertical or horizontal mounting	HP970; HP972
14004407-124	15 to 75% RH	Humidistat Cover assembly Beige with setpoint display and Honeywell logo for vertical mounting. Scale Range 15 to 75% RH	HP970; HP972

Humidistat Accessories

Product Number	Description	Used With	
CCT729A	Gauge Adapter for Calibration. Add 305965 0 to 30 psi gauge for Complete Tool.	HP970, HP972	
CCT735A	Thermostat Calibration Tool includes Allen wrench for cover installation.	HP970, HP972	Honeywell

Replacement Parts

Product Number	Description	Used With		
14002496-001	Nylon element assembly, with Spring	HP970A; HP970B1007		
14002496-003	Nylon element assembly, with Spring	HP970B1005; HP972B		
14002641-001	15 to 75% RH Scaleplate assembly mounted on guard plate	HP970A; HP970B; HP972B		


LP907 Airstream Insertion Pneumatic Thermostat




One-pipe, single setpoint, pneumatic thermostat used to provide proportional control of pneumatic valves and damper actuators in heating and air conditioning systems. Commonly used as discharge controllers for unit ventilators.

- Rod and tube insertion sensing element.
- Wide throttling range.
 Gage tee and tank valve facilitate checking line pressures.

Typical Heating/Cooling Application.



Typical Duct Mounted Application.



Application Type: Low Limit controller

Dimensions, Approximate: 5 7/16 in. high x 1 1/16 in. wide x 2 1/4 in. deep (138 mm high x 27 mm wide x 57 mm deep)

Airflow Usage: 0.011 scfm (5.2 mL/s)

Air Connections: Barb fittings 1/4 in. (6 mm) poly tubing Mounting: Insertion with locknut on boss of insertion shank Operating Temperature: 40 F to 140 F (4 C to 60 C) Storage Temperature: 150 F maximum (66 C maximum)

Remote Bulb: Yes

Sensor Element: Invar rod and seamless brass tube, 18 3/4 in.

(476 mm) long and 11/32 in. (9 mm) diameter Maximum Operating Pressure: 25 psi (170 kPa)

Accessories:

14002913-002 .0.007 in. Red In-line Filtered Restriction Assembly; Inlet: 1/4 in., Outlets: 1/4 in. and 1/4 in.; Order in Quantities of 10

14002913-003 External Restriction Assembly. 0.007 in. Restriction, Red, Inlet 1/4 in; Outlet 1/4 in. and 5/32 in.

CCT2085 Pneumatic Fitting - Gauge Adapter fits any standard 1/8 in. NPT gauge,

Product		Number		Setpoint Temperature Range		Throttling Range	
Number	Action		Setpoint	(F)	Capacity	(F)	Includes
LP907A1002	Direct Acting	1	Single	40 F to 140 F	Low	10 F to 70 F	Fittings for mounting on sheet metal duct. Order restrictor separately.
LP907A1044	Direct Acting	1	Single	40 F to 140 F	Low	5 F to 35 F	Fittings for mounting on sheet metal duct. Order restrictor separately.


Honeywell 70-6925

5


LP916 Pneumatic Thermostat



Typical LP916A Mixed Air Application




Typical LP916B Fan Coil Application, Heating/Cooling with Seasonal Changeover




Two-pipe, single temperature, unit mounted, remote bulb pneumatic thermostat used to provide proportional control of pneumatic valves and damper actuators in heating and air conditioning systems.

- · Liquid filled remote bulb.
- Direct Acting (DA), Reverse Acting (RA) and Heating/Cooling (DA/RA) models are available.

Typical LP916C Fan Coil Application, Cooling Only



Typical LP916A Duct Mounted Heating Application



Application Type: Unit Ventilator

Dimensions, Approximate: 4 3/4 in. high x 3 3/4 in. wide x 3 in. deep (121 mm high x 95 mm wide x 76 mm deep)

Airflow Usage: 0.022 scfm (10.4 mL/s) with 0.007 in. restriction

Air Connections: Barb fittings 1/4 in. (6 mm) Mounting: In compartment of a unit ventilator

Operating Temperature: 135 F maximum (57 C maximum) Storage Temperature: 150 F maximum (66 C maximum)

Remote Bulb: Yes

Sensor Element: Bulb 1/2 x 5 7/8 in., capillary 36 in. (914 mm) long

Setpoint: Single Number of Pipes: 2 Maximum Operating Pressure: 25 psi (170 kPa)

Accessories:

107324A Capillary Holder Assembly for duct insertion, 8 3/8 in. long

14004376-001 Gasket for 14004378 Connector Assembly

14004378-002 Connector Assembly, with integral 0.005 in. restriction and filters for post 1984 units

Replacement Parts:

14003113-002 Repair kit containing 0.007 in. restrictor plate, filters, and gaskets for pre-1984 units

			Setpoi Tempe Range		Changeove		Throt Range			
Product Number	Action	Sensor Element	(F)	(C)	(psi)	(kPa)	(F)	(C)	Includes	Comments
LP916A1019	Direct Acting	Bulb 1/2 x 5 7/8 in., capillary 36 in. (914 mm) long	65 F to 85 F	19 C to 30 C	_	_	3.5 F	2 C	Integral Mounting Bracket and 304528A Bag Assembly (mounting hardware). Order bulb hangers (316297-00021) separately.	_
LP916A1134	Direct Acting	Bulb 3/8 x 7 in., capillary 36 in. (914 mm) long	65 F to 85 F	19 C to 30 C	_	_	3.5 F	2 C	Integral Mounting Bracket, (2) 316297- 00021 Bulb Hangers and 304528A Bag Assembly (mounting hardware).	_
LP916A1175	Direct Acting	Bulb 3/8 x 7 in., capillary 36 in. (914 mm) long	40 F to 80 F	_	_	_	7 F	_	Integral Mounting Bracket, (2) 316297- 00021 Bulb Hangers and 304528A Bag Assembly (mounting hardware).	_
LP916B1017	Direct Acting Heating, Reverse Acting Cooling	Bulb 1/2 x 5 7/8 in., capillary 36 in. (914 mm) long	65 F to 85 F	19 C to 30 C	Heat 18 psi, Cool 13 psi	Heat 124 kPa, Cool 90 kPa	3.5 F	2 C	Integral Mounting Bracket and 304528A Bag Assembly (mounting hardware). Order bulb hangers (316297-00021) separately.	_
LP916B1058	Direct Acting Heating, Reverse Acting Cooling	Bulb 1/2 x 5 7/8 in., capillary 36 in. (914 mm) long	65 F to 85 F	19 C to 30 C	Heat 18 psi, Cool 9 psi	Heat 124 kPa, Cool 62 kPa	3.5 F	2 C	Integral Mounting Bracket and 304528A Bag Assembly (mounting hardware). Order bulb hangers (316297-00021) separately.	_
LP916B1074	Direct Acting Heating, Reverse Acting Cooling	Bulb 3/8 x 7 in., capillary 36 in. (914 mm) long	65 F to 85 F	19 C to 30 C	Heat 18 psi, Cool 13 psi	Heat 124 kPa, Cool 90 kPa	3.5 F	2 C	Order Mounting Bracket, Knob, Bulb Hangers, and Scale Plate separately.	_
LP916B1082	Direct Acting Heating, Reverse Acting Cooling	Bulb 3/8 x 7 in., capillary 36 in. (914 mm) long	65 F to 85 F	19 C to 30 C	Heat 18 psi, Cool 13 psi	Heat 124 kPa, Cool 90 kPa	3.5 F	2 C	Integral Mounting Bracket, (2) 316297- 00021 Bulb Hangers and 304528A Bag Assembly (mounting hardware).	New installation model
LP916B1090	Direct Acting Heating, Reverse Acting Cooling	Bulb 3/8 x 9 in., capillary 36 in. (914 mm) long	65 F to 85 F	19 C to 30 C	Heat 18 psi, Cool 13 psi	Heat 124 kPa, Cool 90 kPa	3.5 F	2 C	Integral Mounting Bracket, (2) 316297- 00021 Bulb Hangers and 304528A Bag Assembly (mounting hardware).	_
LP916C1023	Reverse Acting	Bulb 3/8 x 9 in., capillary 36 in. (914 mm) long	60 F to 80 F	_	_	_	3.5 F	_	Integral Mounting Bracket, (2) 316297- 00021 Bulb Hangers and 304528A Bag Assembly (mounting hardware).	_

Honeywell 70-6925

TP9600 Pneumatic Thermostat



Application Type: Wall Thermostat

Dimensions, Approximate: 3 1/4 in. high x 2 in. wide x 1 5/8 in. deep

(83 mm high x 51 mm wide x 41 mm deep) Airflow Usage: 0.011 scfm (5.2 mL/s) Air Connections: Barb fittings 5/32 in. (4 mm)

Mounting: Vertical Wall Mounting

Operating Temperature: 50 F to 100 F (10 C to 38 C) Storage Temperature: 150 F maximum (66 C maximum)

Remote Bulb: No Sensor Element: Bimetal

Maximum Operating Pressure: 25 psi (170 kPa)

14002913-001 .005 in. Blue Filter Restriction Assembly; Inlet: 1/4 in., Outlets: 1/4 in. and 5/32 in.; Order in Quantities of 10

14002362-001 Duct Sampling Chamber

14002913-004 0.005 in. Blue In-line Filtered Restriction Assembly; Inlet:

1/4 in., Outlets: 5/32 in. and 5/32 in 14002430-001 Thermostat Guard 14004439-001 Setpoint Extension

14004911-001 Taupe Converastat wall plate with 2 screws

Pneumatic thermostat for proportional control of pneumatic valves and actuators with one- or two-pipe systems. Available with two cover options, the TP9600 is not only affordable and easy to install, but it controls temperature with the reliability that only Honeywell can provide.

- TP9600 delivers the Honeywell TP970s unparalleled sensing and control.
- Redesigned models fit your high-volume pneumatic applications. Backplate mounts quickly. Thermostat snaps onto backplate.

- Cover is mounted and locked into place with concealed setscrews.
- Attractive Euro-contoured design comes with choice of two cover options.
- Neutral taupe color blends with today's commercial interiors.
- Adapter kits are available to retrofit most pneumatic jobs. Branchline capacity Low for TP9630 and TP9633 Branchline capacity High for TP9600, TP9610, TP9603, TP9620.

14003192-001 Wallplate adapter kit. Adapts HP970 or TP970 series stats to HP900 and TP900 flush mounted and TP910 series flush or surface mounted installations

305965 1-1/2 in. diameter, 1/8 NPT center stem back mount Pressure Indicating gauge (0 to 30 psi scale) with +/- 4% accuracy

AK3863 Honeywell Thermostat Tool Kit, TP970/TP900

CCT729A Gauge Adapter for Calibration. Add 305965 0 to 30 psi gauge for Complete Tool.

CCT735A Thermostat Calibration Tool includes Allen wrench for cover installation.

Replacement Parts:

14001865-001 Filter Cartridge Assembly

14002053-001 Back Plate Assembly

14002573-001 Modernization Kit to convert all 1 & 2 pipe Honeywell & competitive pneumatic stats to TP970, TP971A, TP972, TP973, TP974, TP9600 family; HP970, HP971 and HP972


14002374-004 Restrictor Block Assembly, 0.005 in., For TP970A-D; TP971A-E except C; TP972A; TP973A-B; TP9600 family; HP970A-B; and HP972B

Product		Number		Setpoint Temperature Range	Changeove	r	Throttling Range	
Number	Action		Setpoint	(F)	(psi)	(kPa)	(F)	Includes
TP9600A1007	Direct Acting	2	Single	60 F to 90 F	_	_	2 F to 10 F	Cover, Setpoint, and Thermometer are Visible
TP9600B1006	Reverse Acting	2	Single	60 F to 90 F	_		2 F to 10 F	Cover, Setpoint, and Thermometer are Visible
TP9603A1001	Direct Acting	2	Single	60 F to 90 F	_	_	2 F to 10 F	Blank Cover, Setpoint, and Thermometer are Not Visible
TP9610A1006	Direct Acting	2	Day/Night	Day: 60 F to 90 F, Night: 50 F to 75 F	Day 13 psi, Night 18 psi	Day 90 kPa, Night 124 kPa	2 F to 10 F	Cover, Setpoint, and Thermometer are Visible
TP9620A1005	Direct Acting Heating, Reverse Acting Cooling	2	Single	60 F to 90 F	Heat 18 psi, Cool 13 psi	Heat 124 kPa, Cool 90 kPa	2 F to 10 F	Cover, Setpoint, and Thermometer are Visible
TP9630A1004	Direct Acting	1 or 2	Single	60 F to 90 F	_		2 F to 10 F	Cover, Setpoint, and Thermometer are Visible
TP9630B1003	Reverse Acting	1 or 2	Single	60 F to 90 F	_	_	2 F to 10 F	Cover, Setpoint, and Thermometer are Visible

TP970 Pneumatic Thermostat



Typical Standard Throttling Range Piping



Application Type: Heating

Dimensions, Approximate: 3 1/4 in. high x 2 in. wide x 1 5/8 in. deep

(83 mm high x 51 mm wide x 41 mm deep) Airflow Usage: 0.011 scfm (5.2 mL/s)

Mounting: Wall

Operating Temperature: 100 F maximum

Storage Temperature: 150 F maximum (66 C maximum)

Remote Bulb: No Sensor Element: Bimetal Setpoint: Single Number of Pipes: 2

Maximum Operating Pressure: 25 psi (170 kPa)

Accessories:

14004439-001 Setpoint Extension 14002430-001 Thermostat Guard

14002362-001 Duct Sampling Chamber

14003192-001 Wallplate adapter kit. Adapts HP970 or TP970 series stats to HP900 and TP900 flush mounted and TP910 series flush or surface mounted installations

14004447-001 Setpoint Cam Assembly for TP970A1004, A1012, A1020, A1038, A1046, A1053, A1095, A2004, A2012, A2020, A2038, A2053, A2095; TP970C; TP972A1143, A2143; TP973A1001, A1019,


14004447-002 Setpoint Cam Assembly for TP970B1002, B1010, B1028, B1036, B2002, B2010, B2028, B2036; TP970D;

Two-pipe, single setpoint, pneumatic thermostat used to provide proportional control of pneumatic valves and damper actuators in heating and air conditioning systems. Replacement kits are available for Johnson, Powers, Robertshaw, Barber-Colman, and older Honeywell two-pipe pneumatic thermostats.

- Honeywell's best pneumatic thermostat-TP970 series.
- Shock-resistant, suspension-mounted thermostats provide dependable performance and responsiveness year in and year out.
- Pilot operated for high capacity.

 Direct Acting (DA) and Reverse Acting (RA) models are available.
- Wide throttling range models for Zero Energy Band (ZEB) operation are available.
- Adapter plate in Convertastat and Modernization kits covers existing thermostat wallmark.
- Backplate has molded air connections-no separate fittings needed.
- Universal locking cover with satin chrome finish and horizontal, vertical, or blank window options.
- Typical Wide Throttling Range Application.

Typical Wide Throttling Range Piping



TP972A1002, A1010, A1028, A1044, A2002, A2010, A2028, A2044; TP973B1009, B1017, B1025, B1108

14004447-005 Setpoint Cam Assembly for TP970B1044; TP972A1051, A1101

305965 1-1/2 in. diameter, 1/8 NPT center stem back mount Pressure Indicating gauge (0 to 30 psi scale) with +/- 4% accuracy

AK3863 Honeywell Thermostat Tool Kit, TP970/TP900

CCT729A Gauge Adapter for Calibration. Add 305965 0 to 30 psi gauge for Complete Tool.

CCT735A Thermostat Calibration Tool includes Allen wrench for cover installation

Replacement Parts:

14001865-001 Filter Cartridge Assembly

14002053-001 Back Plate Assembly

14002374-004 Restrictor Block Assembly, .005 in., For TP970A-D; TP971A-E except C; TP972A; TP973A-B; TP9600 family; HP970A-B; and HP972B

14002573-001 Modernization Kit to convert all 1 & 2 pipe Honeywell & competitive pneumatic stats to TP970, TP971A, TP972, TP973, TP974, TP9600 family; HP970, HP971 and HP972

14004459-001 Repair kit consisting of a thermometer assembly, a thermometer post and a 60 to 90F Aluminum Scaleplate

14004460-001 Nozzle, Throttling Plate and Bimetal Assembly, DA, Left side

9

Honeywell 70-6925

Dueduet		Setpoin Tempera Range		Throttling Ran	ge			
Product Number	Action	(F)	(C)	(F)	(C)	Includes	Comments**	
TP970A2004	Direct Acting	60 F to 90 F	_	2 F to 10 F (factory set 4 F)	_	Order Cover Separately	_	
TP970A2012	Direct Acting	40 F to 70 F	_	2 F to 10 F (factory set 4 F)	_	Order Cover Separately	_	
TP970A2020	Direct Acting		15 C to 30 C		1 C to 5 C (factory set 2 C)	Order Cover Separately	_	
TP970A2038	Direct Acting	60 F to 90 F	_	2 F to 10 F (factory set 4 F)	_	Thermostat, large wall plate and satin chrome cover.	Modernization kit used to convert older Honeywell Thermostats.	
TP970A2053	Direct Acting	60 F to 90 F	_	2 F to 10 F (factory set 4 F)	_	Thermostat, large wall plate and satin chrome cover.	Modernization kit used to convert older Honeywell Thermostats and competitive thermostats.	
TP970A2145	Direct Acting	60 F to 90 F	_	2 F to 10 F (factory set 4 F)	_	Thermostat, small wall plate and satin chrome cover.	Convertastat Kit	
TP970A2234	Direct Acting	_	15 C to 30 C	_	1 C to 5 C (factory set 2 C)	Thermostat, small wall plate and satin chrome cover.	Convertastat Kit	
TP970A2242	Direct Acting	60 F to 90 F	_	2 F to 10 F (factory set 4 F)	_	Thermostat, small wall plate and beige cover.	Convertastat Kit	
TP970A2259	Direct Acting	60 F to 90 F		2 F to 10 F (factory set 4 F)	_	Thermostat and satin chrome cover.	Tradeline Kit	
TP970A2283	Direct Acting	60 F to 90 F	_	2 F to 10 F (factory set 4 F)	_	Thermostat and beige cover.	Tradeline Kit	
TP970B2002	Reverse Acting	60 F to 90 F		2 F to 10 F (factory set 4 F)	_	Order Cover Separately	_	
TP970B2010	Reverse Acting	_	15 C to 30 C		1 C to 5 C (factory set 2 C)	Order Cover Separately	_	
TP970B2077	Reverse Acting	60 F to 90 F	_	2 F to 10 F (factory set 4 F)	_	Thermostat, small wall plate and satin chrome cover.	Convertastat Kit	
TP970B2150	Reverse Acting	_	15 C to 30 C		1 C to 5 C (factory set 2 C)	Thermostat, small wall plate and satin chrome cover.	Convertastat Kit	
TP970B2166	Reverse Acting	60 F to 90 F	_	2 F to 10 F (factory set 4 F)	_	Thermostat, small wall plate and beige cover.	Convertastat Kit	
TP970B2182	Reverse Acting	60 F to 90 F	_	2 F to 10 F (factory set 4 F)	_	Thermostat and satin chrome cover.	Tradeline Kit	
TP970B2216	Reverse Acting	60 F to 90 F	_	2 F to 10 F (factory set 4 F)	_	Thermostat and beige cover.	Tradeline Kit	
TP970C2000	Direct Acting	60 F to 90 F	_	5 F to 25 F	_	Order Cover Separately	Wide Throttling Range 5-25 F	

^{**}A **Tradeline Kit** includes a TP970 Series thermostat with either a Satin Chrome or Beige Universal Cover, Windows (horizontal (F), vertical (F) and blank) for new installations or to convert newer, small size Honeywell or competitor thermostat, not requiring a wall plate adapter.


A **Convertastat Kit**™ includes a TP970 Series thermostat with either a Satin Chrome or Beige Universal Cover, Windows (horizontal (F), vertical (F) and blank) and a small Universal Wall Plate Adapter to convert newer, small size Honeywell or competitor thermostats.

A **Modernization Kit** includes a TP970 Series thermostat with Satin Chrome Universal Cover, Windows (horizontal (F), vertical (F) and blank) and a large Universal Wall Plate Adapter to convert older thermostats.

TP971 Pneumatic Day/Night Thermostat



TP971 Typical Piping



Application Type: Wall Thermostat, Day/Night operation

Dimensions, Approximate: 3 1/4 in. high x 2 in. wide x 1 5/8 in. deep

(83 mm high x 51 mm wide x 41 mm deep) Airflow Usage: 0.011 scfm (5.2 mL/s)

Mounting: Wall

Operating Temperature: 100 F maximum

Storage Temperature: 150 F maximum (66 C maximum)

Remote Bulb: No Setpoint: Day/Night Sensor Element: Bimetal

Maximum Operating Pressure: 25 psi (170 kPa)

14002362-001 Duct Sampling Chamber 14002430-001 Thermostat Guard

Pneumatic thermostat with night setback used to provide proportional control of pneumatic valves and damper actuators in heating and air conditioning systems. Replacement kits are available for Johnson, Powers, Robertshaw, Barber-Colman, and older Honeywell two-pipe pneumatic thermostats.

- Durable TP970 series thermostat Pilot operated for high capacity.
- Direct Acting (DA) and Reverse Acting (RA) models are available. Three-pipe thermostats are available for unit ventilator applications where the outdoor damper must operate when the thermostat is manually set to day operation.

 Adapter plate in thermostat kits covers existing thermostat
- watermark.
- Backplate has molded air connections-no separate fittings needed.
- Universal Locking cover with satin chrome finish and horizontal, vertical, or blank window options-other covers available.

14004439-001 Setpoint Extension

14004447-003 Setpoint Cam Assembly for TP971A, C, D; TP972A1168, A2168, A2176

14003192-001 Wallplate adapter kit. Adapts HP970 or TP970 series stats to HP900 and TP900 flush mounted and TP910 series flush or surface mounted installations

305965 1-1/2 in. diameter, 1/8 NPT center stem back mount Pressure Indicating gauge (0 to 30 psi scale) with +/- 4% accuracy

AK3863 Honeywell Thermostat Tool Kit, TP970/TP900

CCT729A Gauge Adapter for Calibration. Add 305965 0 to 30 psi gauge for Complete Tool.

CCT735A Thermostat Calibration Tool includes Allen wrench for cover installation.

Replacement Parts:

14001865-001 Filter Cartridge Assembly

14002053-001 Back Plate Assembly

14002374-004 Restrictor Block Assembly, .005 in., For TP970A-D; TP971A-E except C; TP972A; TP973A-B; TP9600 family; HP970A-B; and HP972B

14002573-001 Modernization Kit to convert all 1 & 2 pipe Honeywell & competitive pneumatic stats to TP970, TP971A, TP972, TP973, TP974, TP9600 family; HP970, HP971 and HP972

14004460-001 Nozzle, Throttling Plate and Bimetal Assembly, DA, Left

14004460-002 Nozzle, Throttling plate and Bimetal Assembly, reverse acting, left side

Product Number		Number	Setpoint Temperature Range		Changeover	Changeover		ling e		
	Action	of Pipes		(C)	(psi)	(kPa)	(F)	(C)	Includes	Comments**
TP971A2003	Direct Acting Heating, two temp.	2	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 13 psi, Night 18 psi	Day 90 kPa, Night 124 kPa	2 F to 10 F	_	Order Cover Separately	_
TP971A2011	Direct Acting Heating, two temp.	2	_	Day: 15 C to 30 C, Night: 10 C to 27 C	Day 13 psi, Night 18 psi	Day 90 kPa, Night 124 kPa	_	1 C to 5 C	Order Cover Separately	_
TP971A2029	Direct Acting Heating, two temp.	2	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 16 psi, Night 21 psi	Day 110 kPa, Night 144 kPa	2 F to 10 F	_	Order Cover Separately	_
TP971A2052	Direct Acting Heating, two temp.	2	_	Day: 15 C to 30 C, Night: 10 C to 27 C	Day 16 psi, Night 21 psi	Day 110 kPa, 144 kPa	_	1 C to 5 C	Order Cover Separately	_
TP971A2086	Direct Acting Heating, two temp.	2	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 20 psi, Night 25 psi	Day 137 kPa, Night 172 kPa	2 F to 10 F	_	Order Cover Separately	_

Honeywell 70-6925

11

Product		Numaha-	Setpoint Tem Range	perature	Changeover		Thrott Range	ling		
Number	Action	Number of Pipes	(F)	(C)	(psi)	(kPa)	(F)	(C)	Includes	Comments**
TP971A2102	Direct Acting Heating, two temp.	2	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 13 psi, Night 18 psi or 16-20 psi	Day 90 kPa, Night 124 kPa	2 F to 10 F	_	Thermostat, small wall plate and satin chrome cover.	Convertastat Kit
TP971A2183	Direct Acting Heating, two temp.	2	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 13 psi, Night 18 psi or 16-20 psi	Day 90 kPa, Night 124 kPa	2 F to 10 F	_	Thermostat, small wall plate and beige cover.	Convertastat Kit
TP971A2191	Direct Acting Heating, two temp.	2	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 13 psi, Night 18 psi or 16-21 psi	Day 90 kPa, Night 124 kPa	2 F to 10 F	_	Thermostat and satin chrome cover.	Tradeline Kit
TP971B2001	Reverse Acting Heating, two temp.	2	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 13 psi, Night 18 psi	Day 90 kPa, Night 124 kPa	2 F to 10 F	_	Order Cover Separately	_
TP971B2019	Reverse Acting Heating, two temp.	2	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 16 psi, Night 21 psi	Day 110 kPa, Night 144 kPa	2 F to 10 F	_	Order Cover Separately	_
TP971B2043	Reverse Acting Heating, two temp.	2	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 20 psi, Night 25 psi	Day 137 kPa, Night 172 kPa	2 F to 10 F	_	Order Cover Separately	_
TP971B2068	Reverse Acting Heating, two temp.	2	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 13 psi, Night 18 psi or 16-21 psi	Day 90 kPa, Night 124 kPa	2 F to 10 F	_	Thermostat and satin chrome cover.	Tradeline Kit
TP971C2009	Direct Acting Heating, two temp.	3	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 13 psi, Night 18 psi	Day 90 kPa, Night 124 kPa	2 F to 10 F	_	Order Cover Separately	Has secondary branchline
TP971C2017	Direct Acting Heating, two temp.	3	_	Day: 15 C to 30 C, Night: 10 C to 27 C	Day 13 psi, Night 18 psi	Day 90 kPa, Night 124 kPa	_	1 C to 5 C	Order Cover Separately	Has secondary branchline
TP971C2025	Direct Acting Heating, two temp.	3	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 16 psi, Night 21 psi	Day 110 kPa, Night 144 kPa	2 F to 10 F	_	Order Cover Separately	Has secondary branchline
TP971C2058	Direct Acting Heating, two temp.	3	Day: 60 F to 90 F, Night: 50 F to 80 F	_	Day 13 psi, Night 18 psi or 16-21 psi	Day 90 kPa, Night 124 kPa	2 F to 10 F	_	Thermostat and Satin Chrome Cover	Tradeline Kit. Has secondary branchline.

^{**}A **Tradeline Kit** includes a TP970 Series thermostat with either a Satin Chrome or Beige Universal Cover, Windows (horizontal (F), vertical (F) and blank) for new installations or to convert newer, small size Honeywell or competitor thermostat, not requiring a wall plate adapter.


A **Convertastat Kit**™ includes a TP970 Series thermostat with either a Satin Chrome or Beige Universal Cover, Windows (horizontal (F), vertical (F) and blank) and a small Universal Wall Plate Adapter to convert newer, small size Honeywell or competitor thermostats.

A **Modernization Kit** includes a TP970 Series thermostat with Satin Chrome Universal Cover, Windows (horizontal (F), vertical (F) and blank) and a large Universal Wall Plate Adapter to convert older thermostats.

TP972 Pneumatic Heating/Cooling Thermostat



TP972 Typical Piping



Accessories:

14002362-001 Duct Sampling Chamber

14002430-001 Thermostat Guard

14003923-001 20 to 25 psi spring

14004439-001 Setpoint Extension

- 14003192-001 Wallplate adapter kit. Adapts HP970 or TP970 series stats to HP900 and TP900 flush mounted and TP910 series flush or surface mounted installations
- **14004447-001** Setpoint Cam Assembly for TP970A1004, A1012, A1020, A1038, A1046, A1053, A1095, A2004, A2012, A2020, A2038, A2053, A2095; TP970C; TP972A1143, A2143; TP973A1001, A1019, A1127
- **14004447-002** Setpoint Cam Assembly for TP970B1002, B1010, B1028, B1036, B2002, B2010, B2028, B2036; TP970D; TP972A1002, A1010, A1028, A1044, A2002, A2010, A2028, A2044; TP973B1009, B1017, B1025, B1108
- **14004447-003** Setpoint Cam Assembly for TP971A, C, D; TP972A1168, A2168, A2176
- **14004447-005** Setpoint Cam Assembly for TP970B1044; TP972A1051, A1101

Two-pipe, one- or two-temperature, pneumatic thermostat used to provide proportional control of pneumatic valves and damper actuators in heating and air conditioning systems. Replacement kits are available for Johnson, Powers, Robertshaw, Barber-Colman, and older Honeywell two-pipe pneumatic thermostats.

- Durable TP970 Series Thermostat. Pilot operated for high capacity.
- Two-temperature energy conservation model available.
- Adapter plate in Convertastat kits covers existing thermostat wallmark.
- · Backplate has molded air connections-no separate fittings needed.
- Universal locking cover with satin chrome finish and horizontal, vertical, or blank window options with Tradeline model-other covers available.

Application Type: Wall Thermostat, Heat/Cool Operation

Dimensions, Approximate: 3 1/4 in. high x 2 in. wide x 1 5/8 in. deep

(83 mm high x 51 mm wide x 41 mm deep)

Action: Direct Acting Heating, Reverse Acting Cooling

Airflow Usage: 0.011 scfm (5.2 mL/s)

Mounting: Wall

Operating Temperature: 100 F maximum

Storage Temperature: 150 F maximum (66 C maximum)

Remote Bulb: No

Sensor Element: Bimetal

Maximum Operating Pressure: 25 psi (170 kPa)

305965 1-1/2 in. diameter, 1/8 NPT center stem back mount Pressure Indicating gauge (0 to 30 psi scale) with +/- 4% accuracy

AK3863 Honeywell Thermostat Tool Kit, TP970/TP900

CCT729A Gauge Adapter for Calibration. Add 305965 0 to 30 psi

gauge for Complete Tool.

CCT735A Thermostat Calibration Tool includes Allen wrench for cover installation.

Replacement Parts:

14001865-001 Filter Cartridge Assembly

14002374-004 Restrictor Block Assembly, 005 in., For TP970A-D; TP971A-E except C; TP972A; TP973A-B; TP9600 family; HP970A-B; and HP972B

- **14002573-001** Modernization Kit to convert all 1 & 2 pipe Honeywell & competitive pneumatic stats to TP970, TP971A, TP972, TP973, TP974, TP9600 family; HP970, HP971 and HP972
- 14004460-001 Nozzle, Throttling Plate and Bimetal Assembly, DA, Left side
- 14004460-002 Nozzle, Throttling plate and Bimetal Assembly, reverse acting, left side

Product	Number	Set-	Setpoint Te Range	mperature	Changeover		Changeover		Changeover		Throttling Range			
Number		point	(F)	(C)	(psi)	(kPa)	(F)	(C)	Includes	Comments**				
TP972A2002	2	Single	60 F to 90 F	_	Heat 18 psi, Cool 13 psi	Heat 124 kPa, Cool 90 kPa	2 F to 10 F	_	Order Cover Separately	_				
TP972A2010	2	Single	_	15 C to 30 C	Heat 18 psi, Cool 13 psi	Heat 124 kPa, Cool 90 kPa	_	1 C to 5 C	Order Cover Separately	_				
TP972A2036	2	Dual	Heating 50 F to 75 F, Cooling 60 F to 90 F	_	Heat 18 psi, Cool 13 psi	Heat 124 kPa, Cool 90 kPa	2 F to 10 F	_	Energy Conservation Model, Order Cover Separately	Two concealed setpoint knobs				

70-6925 **Honeywell**

13

Product	Number	Set-	Setpoint Te Range	mperature	Changeover			Changeover						Throttling Range								
Number	2.1	point	(F)	(C)	(psi)	(kPa)	(F)	(C)	Includes	Comments**												
TP972A2143	2	Single	60 F to 90 F	_	Heat 14 psi, Cool 19 psi	Heat 96 kPa, Cool 131 kPa	2 F to 10 F	_	Order Cover Separately	_												
TP972A2192	2	Single	60 F to 90 F	_	Heat 18 psi, Cool 13 psi	Heat 124 kPa, Cool 90 kPa	2 F to 10 F	_	Thermostat, small wall plate and satin chrome cover	Convertastat Kit												
TP972A2226	2	Single	60 F to 90 F	_	Heat 14 psi, Cool 19 psi	Heat 96 kPa, Cool 131 kPa	2 F to 10 F		Thermostat and satin chrome cover.	Tradeline Kit												
TP972A2242	2	Single	60 F to 90 F	_	Heat 18 psi, Cool 13 psi	Heat 124 kPa, Cool 90 kPa	2 F to 10 F	_	Thermostat and satin chrome cover.	Tradeline Kit												

^{**}A **Tradeline Kit** includes a TP970 Series thermostat with either a Satin Chrome or Beige Universal Cover, Windows (horizontal (F), vertical (F) and blank) for new installations or to convert newer, small size Honeywell or competitor thermostat, not requiring a wall plate adapter.


A **Convertastat Kit**™ includes a TP970 Series thermostat with either a Satin Chrome or Beige Universal Cover, Windows (horizontal (F), vertical (F) and blank) and a small Universal Wall Plate Adapter to convert newer, small size Honeywell or competitor thermostats.

A **Modernization Kit** includes a TP970 Series thermostat with Satin Chrome Universal Cover, Windows (horizontal (F), vertical (F) and blank) and a large Universal Wall Plate Adapter to convert older thermostats.

TP973 Pneumatic Thermostat



TP973 Typical Piping (One-pipe)



Accessories:

14002913-004 0.005 in. Blue In-line Filtered Restriction Assembly; Inlet: 1/4 in., Outlets: 5/32 in. and 5/32 in

14002430-001 Thermostat Guard

14002362-001 Duct Sampling Chamber

14003192-001 Wallplate adapter kit. Adapts HP970 or TP970 series stats to HP900 and TP900 flush mounted and TP910 series flush or surface mounted installations

14004447-001 Setpoint Cam Assembly for TP970A1004, A1012, A1020, A1038, A1046, A1053, A1095, A2004, A2012, A2020, A2038, A2053, A2095; TP970C; TP972A1143, A2143; TP973A1001, A1019, A1127

14004447-002 Setpoint Cam Assembly for TP970B1002, B1010, B1028, B1036, B2002, B2010, B2028, B2036; TP970D; TP972A1002, A1010, A1028, A1044, A2002, A2010, A2028, A2044; TP973B1009, B1017, B1025, B1108

14004439-001 Setpoint Extension

305965 1-1/2 in. diameter, 1/8 NPT center stem back mount Pressure Indicating gauge (0 to 30 psi scale) with +/- 4% accuracy

One- or two-pipe, single temperature, low capacity, pneumatic thermostat used to provide proportional control of pneumatic valves and damper actuators in heating and air conditioning systems. Replacement kits are available for Johnson, Powers, Robertshaw, Barber-Colman, and older Honeywell pneumatic thermostats.

- Durable TP970 Series Thermostat. Direct Acting (DA) and Reverse Acting (RA) models are available.
- Backplate has molded air connections-no separate fittings needed.
 Universal locking cover with satin chrome finish and horizontal,
- vertical, or blank window options available.
- Other Covers Available.
- Low capacity thermostat.
- Built in restrictor for two-pipe applications.

Application Type: Wall Thermostat, Single Temperature

Dimensions, Approximate: 3 1/4 in. high x 2 in. wide x 1 5/8 in. deep

(83 mm high x 51 mm wide x 41 mm deep) **Airflow Usage:** 0.011 scfm (5.2 mL/s)

Mounting: Wall

Operating Temperature: 100 F

Storage Temperature: 150 F maximum (66 C maximum)

Setpoint: Single Number of Pipes: 1 or 2 Remote Bulb: No Sensor Element: Bimetal

Maximum Operating Pressure: 25 psi (170 kPa)

AK3863 Honeywell Thermostat Tool Kit, TP970/TP900

CCT729A Gauge Adapter for Calibration. Add 305965 0 to 30 psi gauge for Complete Tool.

CCT735A Thermostat Calibration Tool includes Allen wrench for cover installation.

Replacement Parts:

14001865-001 Filter Cartridge Assembly

14002053-001 Back Plate Assembly

14002573-001 Modernization Kit to convert all 1 & 2 pipe Honeywell & competitive pneumatic stats to TP970, TP971A, TP972, TP973, TP974, TP9600 family; HP970, HP971 and HP972

14002374-004 Restrictor Block Assembly, 005 in., For TP970A-D; TP971A-E except C; TP972A; TP973A-B; TP9600 family; HP970A-B; and HP972B

14004460-001 Nozzle, Throttling Plate and Bimetal Assembly, DA, Left

14004460-002 Nozzle, Throttling plate and Bimetal Assembly, reverse acting, left side

Product		Setpoint Temperature Range		Throttling Range				
Number	Action	(F)	(F) (C) (F) (C)		(C)	Includes	Comments**	
TP973A2076	Direct Acting	60 F to 90 F	_	2 F to 10 F	_	Order Cover Separately	For one-pipe order an external .005 in. restriction	
TP973A2084	Direct Acting		15 C to 30 C	_	1 C to 5 C	Order Cover Separately	For one-pipe order an external .005 in. restriction	
TP973A2167	Direct Acting	60 F to 90 F	_	2 F to 10 F	_	Thermostat and cover # 14004407-121	For one-pipe order an external .005 in. restriction	
TP973A2209	Direct Acting	60 F to 90 F	_	2 F to 10 F	_	Thermostat and Satin Chrome Cover	Tradeline Kit. For one-pipe application- order an external .005 in. restriction	
TP973A2223	Direct Acting	60 F to 90 F	_	2 F to 10 F	_	Thermostat and beige cover	Tradeline Kit. For one-pipe application- order an external .005 in. restriction	

70-6925 Honeywell

15

Draduct	Dura dura 4		Setpoint Temperature Range		Range		
Product Number	Action	(F)	(C)	(F)	(C)	Includes	Comments**
TP973B2066	Reverse Acting	60 F to 90 F	_	2 F to 10 F	_	Order Cover Separately	For one-pipe order an external .005 in. restriction
TP973B2074	Reverse Acting	_	15 C to 30 C	_	1 C to 5 C	Order Cover Separately	For one-pipe order an external .005 in. restriction
TP973B2132	Reverse Acting	60 F to 90 F	_	2 F to 10 F		Thermostat and cover # 14004407-121	For one-pipe order an external .005 in. restriction
TP973B2171	Reverse Acting	60 F to 90 F	_	2 F to 10 F	_	Thermostat and Satin Chrome Cover	Tradeline Kit. For one-pipe application- order an external .005 in. restriction

^{**}A **Tradeline Kit** includes a TP970 Series thermostat with either a Satin Chrome or Beige Universal Cover, Windows (horizontal (F), vertical (F) and blank) for new installations or to convert newer, small size Honeywell or competitor thermostat, not requiring a wall plate adapter.

A **Convertastat Kit™** includes a TP970 Series thermostat with either a Satin Chrome or Beige Universal Cover, Windows (horizontal (F), vertical (F) and blank) and a small Universal Wall Plate Adapter to convert newer, small size Honeywell or competitor thermostats.

A **Modernization Kit** includes a TP970 Series thermostat with Satin Chrome Universal Cover, Windows (horizontal (F), vertical (F) and blank) and a large Universal Wall Plate Adapter to convert older thermostats.


TP975 Pneumatic Diffuser Thermostat



One-pipe, single temperature, low-capacity pneumatic thermostat used to provide proportional control of pneumatic valves and mixing boxes in heating and air conditioning systems. It mounts in a slot or light troffer diffuser or a return air grill.

- Two-way setpoint indicator for vertical or horizontal mounting. Detents in 1 F (0.5 C) increments for blind operation.

TP975 Typical Piping



Application Type: Single temperature, low capacity, pneumatic

thermostat

Dimensions, Approximate: 1 in. high x 2 1/2 in. wide x 1 1/8 in. deep

(25 mm high x 63 mm wide x27 mm deep) Airflow Usage: 0.011 scfm (5.2 mL/s)

Mounting: Wall

Operating Temperature: 110 F maximum (43 C maximum) Storage Temperature: 150 F maximum (66 C maximum)

Remote Bulb: No Sensor Element: Bimetal

Maximum Operating Pressure: 30 psi (207 kPa)

Accessories:

14002913-001 .005 in. Blue Filter Restriction Assembly; Inlet: 1/4 in.,

Outlets: 1/4 in. and 5/32 in.; Order in Quantities of 10

14002913-004 0.005 in. Blue In-line Filtered Restriction Assembly; Inlet: 1/4 in., Outlets: 5/32 in. and 5/32 in

		Number		Setpoint Temperature Range	Throttling Range	
Product Number	Action		Setpoint	(F)	(F)	Comments
TP975A1009	Direct Acting	1	Single	67 F to 83 F	2 F to 10 F	Requires external 0.005 in. restrictor

Honeywell 70-6925 17

Pneumatic Thermostat Accessories

Product Number	Description	Used With	
14001491-002	Two-Pipe Airhead, plastic tubing assembly for deep wall box	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	PROTECTIVE CAP OR CAPS OR CAPS PROVIDED SNAP RING (FITS KNOCKOUT FOR 1/2 INCH CONDUIT) B FEET [2.5 M] MS477 BRASS ELBOW
14001494-002	2 Pipe Airhead Assembly, copper tubing for deep wall box.	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14001496-001	Mounting Plate for TP970 to 2" x 4" Electrical Box	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14001527-001	Three pipe straight white connector	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	C5356
14001614-001	Shallow wall plate assembly	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14001615-001	One-pipe copper tube assembly for shallow wall box	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14001615-002	Two-pipe cooper tube assembly for shallow wall	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14001616-002	Two-pipe plastic tube assembly for shallow wall box	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14001918-001	Branchline pressure plug	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14002136-004	Black Trim plate	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14002136-005	Beige Trim plate	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14002136-006	Premier White Trim Plate	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14002136-007	Taupe Trim Plate	TP9600 Family	
14002172-001	Gage Tap repair plug	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14002362-001	Duct Sampling Chamber	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14002373-001	Switch over Springs 16 To 21 Psi,	TP972; TP971	
14002390-001	Bag assembly of screws	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	

Product Number	Description	Used With	
14002430-001	Thermostat Guard	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14002573-002	Modernization Kit to convert 3 pipe Honeywell TP911C & competitive three pipe pneumatic thermostats to TP971C	TP971C	
14002636-001	Base for 14002362-001 Sampling Chamber	14002362-001	
14002913-001	0.005 in. Blue In-line Filtered Restriction Assembly; Inlet: 1/4 in., Outlets: 1/4 in. and 5/32 in.; Order in Quantities of 10	In-line restriction applications	
14002913-002	0.007 in. Red In-line Filtered Restriction Assembly; Inlet: 1/4 in., Outlets: 1/4 in. and 1/4 in.; Order in Quantities of 10	In-line restriction applications	
14002913-003	0.007 in. Red In-line Filtered Restriction Assembly; Inlet: 1/4 in., Outlets: 1/4 in. and 5/32 in.; Order in Quantities of 10	In-line restriction applications	
14002913-004	0.005 in. Blue In-line Filtered Restriction Assembly; Inlet: 1/4 in., Outlets: 5/32 in. and 5/32 in.; Order in Quantities of 10	In-line restriction applications	
14002913-005	0.007 in. Red In-line Filtered Restriction Assembly; Inlet: 1/4 in., Outlets: 5/32 in. and 5/32 in.; Order in Quantities of 10	In-line restriction applications	
14003113-002	Repair kit containing 0.007 in. restrictor plate, filters, and gaskets for pre-1984 units	LP916	
14003203-001	Bag assembly used in 14003192-001	_	
14003203-003	Conversion Kit to convert Johnson, Powers, Robertshaw, Barber Coleman and older Honeywell switches	_	
14003929-001	Bimetal TP928	TP928	
14004056-001	Dual Cover Assembly; Beige, 60F to 90F thermometer and setpoint display	TP979	
14004056-007	Dual Cover Assembly; Beige, with Honeywell Logo only (no temperature displays)	TP979	
14004056-008	Dual Cover Assembly; Beige, blank (no temperature displays and no logo)	TP979	
14004068-001	Mounting assembly	TP979	
14004193-001	Stand-Off Ring	TP979	
14004376-001	Gasket for 14004378 Connector Assembly	LP916	
14004378-002	Connector Assembly, with integral 0.005 in. restriction and filters for post 1984 units	LP916	
14004401-002	Convertastat wall plate, Black		

70-6925 **Honeywell** 19

Product Number	Description	Used With	
14004401-004	Convertastat wall plate, Beige	_	
14004402-001	Thermostat Cover Satin Chrome, no windows	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14004437-001	Insert Cover, Day, Auto, Satin Chrome	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14004438-001	Insert Cover, Satin Chrome, Setpoint Display	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14004438-002	Insert Cover, Beige, Setpoint Display	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14004439-001	Setpoint Extension	TP970; TP971; TP972; TP973; TP9600	
14004441-001	Window inserts for use on Satin Chrome Cover fahrenheit scale (60 to 90 F) for vertical and horizontal mounting.	TP970; TP971; TP972; TP973	Horsveril American Ameri
14004441-002	Window inserts for use on Satin Chrome Cover fahrenheit scale (60 to 90 F) for vertical and horizontal mounting. Includes cover insert for setpoint slot	TP970; TP971; TP972; TP973	Manage of the second of the se
14004447-001	Setpoint Cam Assembly for TP970A1004, A1012, A1020, A1038, A1046, A1053, A1095, A2004, A2012, A2020, A2038, A2053, A2095; TP970C; TP972A1143, A2143; TP973A1001, A1019, A1127	TP970A; TP970C; TP972A2143; TP979A	
14004447-002	Setpoint Cam Assembly for TP970B1002, B1010, B1028, B1036, B2002, B2010, B2028, B2036; TP970D; TP972A1002, A1010, A1028, A1044, A2002, A2010, A2028, A2044; TP973B1009, B1017, B1025, B1108	TP970B; TP970D; TP972A2002; TP972A2010; TP973B2108; TP979B	
14004447-003	Setpoint Cam Assembly for TP971A, C, D; TP972A1168, A2168, A2176	TP971A; TP971C; TP971D	
14004447-005	Setpoint Cam Assembly for TP970B1044; TP972A1051, A1101	TP970B; TP972A	
14004458-001	Stand-Off Ring for surface or flush mounting	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	CB404
14004505-001	Twin elbow connector	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14004558-001	Six inch branch tube-spring assembly	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	

Product Number	Description	Used With	I
14004729-002	Cover Screw	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14004756-002	Dual Cover Assembly; Satin Chrome, 15 - 30 C thermometer and setpoint scales	TP979	
14004756-005	Dual Cover Assembly; Satin Chrome, 60 - 90F thermometer scale	TP979	
14004756-008	Dual Cover Assembly; Satin Chrome, Blank, no temperature scales or logo.	TP979	
14004908-001	Stop Kit	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14004911-001	Taupe Converastat wall plate with 2 screws	TP9600 Family	
311699	Tubing Spring	LP916	
314826	Diaphragm	LP916	
315949	Scaleplate for TP928	TP928	
316016A	General purpose mounting assembly, includes 3 3/4 in. mounting bracket, scale plate, knob, bulb hangers, screws, and nuts	LP916	
316016C	Knob and scale plate assembly with screws	LP916	
316016M	Knob, large scale plate and hanger assembly with screws	LP916	
43176655-004	Case	TP937, TP938	
AK3863	Honeywell Thermostat Tool Kit, TP970/TP900	HP970, HP972, TP970	
AK3970	Cover for Aspirator Boxes 14002424-002 and 14002424-003	14002424-002; 14002424-003	

70-6925 **Honeywell** 21

Pneumatic Thermostat Replacement Parts

Product Number	Description	Used With	
14000742-002	Two-pipe red airhead with back connection	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14001865-001	Filter Cartridge Assembly	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14001957-001	Plug, BLP Tap,	TP970	
14002053-001	Back Plate Assembly	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	BACKPLATE M5479
14002111-024	Window with 60 to 90F thermometer scale for use on old aluminum style 14001984 thermostat covers.	14001984 cover	
14002374-004	Restrictor Block Assembly, 005 in., 2-pipe for TP970A-D; TP971A-E except C; TP972A; TP973A-B; TP9600 family; HP970A-B; and HP972B	TP970	
14002374-005	Restrictor Block Assembly, .005 in., 3-pipe for TP971C	TP971C	
14002420-001	Mounting. Plate assembly, with mounting plate (14002421-001), 4 clips (14002422-001), 4 rivets (305835)	14002424-001	
14002573-001	Modernization Kit to convert all 1 & 2 pipe Honeywell & competitive pneumatic stats to TP970, TP971A, TP972, TP973, TP974, TP9600 family; HP970, HP971 and HP972	TP970; TP9600; TP972; HP970; HP971; TP971A; HP972; TP973; TP974	
14003192-001	Wallplate adapter kit. Adapts HP970 or TP970 series stats to HP900 and TP900 flush mounted and TP910 series flush or surface mounted installations	TP970; TP971; TP972; TP973; TP9600 Family; HP970 Family	
14003194-001	TP910 black base plate	TP910	
14003195-001	TP910 beige base plate	TP910	
14003923-001	20 to 25 psi spring	TP971	
14004405-005	Window insert for use on Satin Chrome cover 14004402-002. Window has fahrenheit scale (60 to 90F) for thermometer; setpoint display and a Honeywell logo	TP970; TP971; TP972; TP973	
14004447-006	Setpoint Cam Assembly for TP973A2076, A2084, A2209, and A2223	TP973A	
14004447-007	Setpoint Cam Assembly for TP973B2068, B2074, B2132, B2171 and TP9630B1003	TP973B; TP9630B1003	
14004459-001	Repair kit consisting of a thermometer assembly, a thermometer post and a 60 to 90F Aluminum Scaleplate	TP970; TP973	
14004459-003	Repair KIt consisting of a thermometer assembly, a thermometer post and a 15 to 30 C Aluminum Scaleplate	TP970; TP973	
14004460-001	Nozzle, Throttling Plate and Bimetal Assembly, DA, Left side	TP970A,TP971A, C, D, TP972 DA, left side, TP973A, TP979A	
14004460-002	Nozzle, Throttling plate and Bimetal Assembly, reverse acting, left side	TP970B, TP971B, TP972 RA, left side, TP973B, TP979B	

Product Number	Description	Used With	
14004460-003	Nozzle, Throttling plate and Bimetal Assembly, DA, right side	TP972	
14004609-001	Steel Stiffener plate	TP970; TP971; TP972; TP973; TP9600	
14004610-001	Zinc plate metal stud Adapter	TP970; TP971; TP972; TP973; TP9600	
303627	Gasket for LP901	LP901	

TP9600 Series Standard Covers

Product Number	Description	Used With	
14004910-001	Fahrenheit scale (60 to 90 F) Taupe Thermostat Cover Kit with thermometer and setpoint display visible and Honeywell logo for vertical mounting.	TP9600	30 70 30 90 Honeywell
14004910-004	Taupe Thermostat Cover with setpoint and thermometer concealed with Honeywell logo, for vertical mounting	TP9600	Honeywell

70-6925 **Honeywell** 23

TP970 Series Standard Covers

Product Number	Description	Comments	Used With	
14003925-002	Thermostat Cover Kit - Satin Chrome includes window inserts for 60 to 90 F thermometer and setpoint display and inserts for just the Honeywell logo (vertical and horizontal mounting)	_	TP970; TP972; TP971; TP973	
14004406-110	Celsius scale (15-30 C) Satin Chrome Thermostat Cover Kit with Thermometer Display and setpoint display and Honeywell logo for vertical mounting. Open setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	15 20 25 30 Honeywell 15 20 25 30 _{M18939}
14004406-111	Fahrenheit scale (60 to 90 F) Satin Chrome Thermostat Cover Kit with Thermometer Display and setpoint display and Honeywell logo for vertical mounting. Open setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	60 70 80 90 Honeywell 60 70 80 90 M18935
14004406-112	Fahrenheit scale (40 to 70 F) Satin Chrome Thermostat Cover Kit with thermometer display, setpoint display and Honeywell logo for vertical mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	40 50 60 70 Honeywell 40 50 60 70 M18962
14004406-115	Fahrenheit scale (60F to 90F). Display has large scale numerals for the visually impaired. Has thermometer display, setpoint display and Honeywell logo for vertical mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	Honeywell 60 75 90
14004406-120	Celsius scale (15 to 30C) Satin Chrome Thermostat Cover Kit with setpoint display and Honeywell logo for vertical mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	Honeywell 15 20 25 30 M18941
14004406-121	Fahrenheit scale (60 to 90F) Satin Chrome Thermostat Cover Kit with setpoint display and Honeywell logo for vertical mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	Honeywell 60 70 80 90 M18938

Product Number	Description	Comments	Used With	
14004406-122	Fahrenheit scale (40 to 70F) Satin Chrome Thermostat Cover Kit with setpoint display and Honeywell logo for vertical mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	Honeywell 40 50 60 70 M18964
14004406-123	Satin Chrome Thermostat Cover Kit with setpoint display and Honeywell logo for vertical mounting with Warmer/Cooler Scale. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	Honeywell Cooler Warmer M18970
14004406-210	Celsius scale (15 to 30 C) Satin Chrome Thermostat Cover kit with thermometer and setpoint display and Honeywell logo for horizontal mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	30 30 25 20 15 15 M13901
14004406-211	Fahrenheit scale (60 to 90F) Satin Chrome Thermostat Cover Kit with thermometer display, setpoint display and Honeywell logo for horizontal mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	90 90 80 70 60 60 M18968
14004406-310	Celsius scale (15 to 30C) Satin Chrome Thermostat Cover Kit with thermometer display, setpoint display and Honeywell logo for vertical mounting. Closed Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	15 20 25 30 Honeywell 15 20 25 30 M18939
14004406-311	Fahrenheit scale (60 to 90C) Satin Chrome Thermostat Cover Kit with thermometer display, setpoint display and Honeywell logo for vertical mounting. Closed Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	60 70 80 90 Honeywell 60 70 80 90 M18935
14004406-321	Fahrenheit scale (60 to 90F) Satin Chrome Thermostat Cover Kit with setpoint display and Honeywell logo for vertical mounting. Closed Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	Honeywell 60 70 80 90 M18938
14004406-330	Celsius scale (15 to 30C) Satin Chrome Thermostat Cover Kit with thermometer display and Honeywell logo for vertical mounting. Closed Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	15 20 25 30 Honeywell

70-6925 **Honeywell** 25

Product Number	Description	Comments	Used With	
14004406-331	Fahrenheit scale (60 to 90F), Satin chrome thermostat cover kit with thermometer display and Honeywell logo for vertical mounting. Closed Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	60 70 80 90 Honeywell
14004406-511	Fahrenheit scale (60 to 90F), Satin Chrome Thermostat Cover Kit with thermometer display, setpoint display. No logo for vertical mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	60 70 80 90 60 70 80 90 _{M18965}
14004406-611	Fahrenheit scale (60 to 90F), Satin Chrome Thermostat Cover Kit with thermometer display, setpoint display and no logo for horizontal mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	90 90 80 70 70 60 60 60
14004406-711	Fahrenheit scale (60 to 90F), Satin Chrome Thermostat Cover Kit with thermometer and setpoint display and no logo for vertical mounting. Closed Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	60 70 80 90 60 70 80 90 _{M18965}
14004406-910	Thermostat cover kit, Satin Chrome include a cover, setpoint cover and 6 window inserts for 60 to 90F scale for vertical and horizontal mounting.	_	TP970; TP972; TP971; TP973	I I I I I I I I I I I I I I I I I I I
14004407-110	Celsius scale (15 C to 30 C), Beige Thermostat Cover Kit with thermometer display, setpoint display and Honeywell logo for vertical mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	15 20 25 30 Honeywell 15 20 25 30 M18939
14004407-111	Fahrenheit scale (60 F to 90 F), Beige Thermostat Cover Kit with thermometer display, setpoint display and Honeywell logo for vertical mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	60 70 80 90 Honeywell 60 70 80 90

Product Number	Description	Comments	Used With	
14004407-121	Fahrenheit scale (60 F to 90 F), Beige Thermostat Cover Kit with setpoint display and Honeywell logo for vertical mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	Honeywell 60 70 80 90 M18938
14004407-210	Celsius scale (15 to 30 C) Beige Thermostat Cover Kit with thermometer and setpoint display and Honeywell logo for horizontal mounting. Open Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	30 30 25 25 20 15 15 M13901
14004407-300	Beige Cover Kit with Honeywell logo for vertical mounting. Closed Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973; HP970; HP972	Honeywell M18937
14004407-311	Fahrenheit scale (60 F to 90 F), Beige Thermostat Cover Kit with thermometer display, setpoint display and Honeywell logo for vertical mounting. Closed Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	60 70 80 90 Honeywell 60 70 80 90 M18935
14004407-511	Fahrenheit scale (60 F to 90 F), Beige Thermostat Cover Kit with thermometer display and setpoint display for vertical mounting. Closed Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	60 70 80 90 60 70 80 90 _{M18965}
14004407-800	Beige Cover Kit with no display and no logo for vertical or horizontal mounting. Closed Setpoint slot.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973; HP970; HP972	M18967

70-6925 **Honeywell** 27

Product Number	Description	Comments	Used With	
14004407-910	Thermostat Cover Kit - Beige includes cover, setpoint insert cover and 6 window inserts for 60 to 90 F scale for vertical and horizontal mounting.	See Specification Data sheet, Form No. 77-1003 for details	TP970; TP972; TP971; TP973	Annual Control of the
14004787-910	Thermostat Cover Kit - Bright Chrome includes cover, setpoint insert cover and 6 window inserts for 60 to 90 F scale for vertical and horizontal mounting.		TP970; TP972; TP971; TP973	
14004878-700	Premiere White Cover Kit with no display and no logo for vertical or horizontal mounting. Closed Setpoint slot.		TP970; TP972; TP971; TP973; HP970; HP972	M18967
14004878-910	Thermostat Cover Kit - Premier White includes cover, setpoint insert cover and 6 window inserts for 60 to 90 F scale for vertical and horizontal mounting.		TP970; TP972; TP971; TP973	