

FILTRATION SPECIFICATIONS

Filter: Model 4 Basket Strainers and Bag Filters

Model 4 strainer/filter housings are made in 2 basket sizes and 4 pressure ratings. In all cases, covers are easily removed without special tools, and the basket or bag is easily cleaned or replaced.

FEATURES

- Carbon steel or stainless steel (304 or 316) construction for housings
- O-ring seals: Buna N, EPR, Fluoroelastomer, PTFE
- Two pressure ratings: 200 psi (with clamp cover) and 500 psi (with eyenut cover)
- Pipe sizes 1-inch thru 2-inch, NPT
- Two basket depths: 6 or 12 inches

OPTIONS

- Liquid Displacers
- Magnets
- Adjustable Legs
- ASME Code Stamp







FILTRATION SPECIFICATIONS

Filter: Model 4 Basket Strainers and Bag Filters


PRESSURE DROP DATA

Basket strainers and bag filters are usually selected so that the pressure drop does not exceed 2 psi when they are clean. Higher pressure drops may be tolerated when contaminant loading is low. Bag change-out should occur at 15 psid.

The pressure drop data is determined by the steps below:

FOLLOW THESE EASY STEPS:

- 1. Using the desired pipe size and approximate flow rate, determine the pressure drop from the appropriate graph.
- 2. Multiply the pressure drop obtained in step 1 by the viscosity correction factor found in the accompanying table. This is the adjusted pressure drop for all baskets, without filter bags.
- 3. Add the pressure drop for the bag filter housing.



*Based on housing only. Fluid viscosity, bag filter used, and expected dirt loading should be considered when sizing a filter.



Clamp covers on the left and center, eyenut cover on the right.

Filter bags are specified and sold separately.

	VISCOSITY, CPS								
BAG STYLE	1 (H₂O)	50	100	200	400	600	800	1000	2000
ALL UNLINED BASKETS	.65	.85	1.00	1.10	1.20	1.40	1.50	1.60	1.80
40-MESH LINED	.73	.95	1.20	1.40	1.50	1.80	1.90	2.00	2.30
60-MESH LINED	.77	1.00	1.30	1.60	1.70	2.10	2.20	2.30	2.80
80-MESH LINED	.93	1.20	1.50	1.90	2.10	2.40	2.60	2.80	3.50
100- MESH LINED	1.00	1.30	1.60	2.20	2.40	2.70	3.00	3.30	4.40
200- MESH LINED	1.30	1.70	2.10	3.00	3.40	3.80	4.40	5.00	6.80



Model 4 - Dimensions


COVER TYPES


Eyenut Clamp Cover Cover 500 Series with Rated 200 PSI with pipe threads NPT connections Gage Ports 1/4" NPT 8" Centers 14.0 (3) 5/16 dia. holes on 6.75 dia. Bolt Circle


- 9.50-

OUTLET STYLES

Threaded NPT Connections







A clearance distance equal to the basket depth must be available above the housing for basket removal. Legs for the Model 4 are optional at an extra cost.

Model Size	Pipe	Α	A1	A2	В	С	D	E	F	G	Н	L	М
	1	5.5	1.9	2.3	3.5	5.0	10.3	12.0	4.5	10.1	10.9	4.0	2.5
4.6	1 1/4	6.1	2.5	2.9	3.5	5.0	9.7	12.0	4.5	9.4	10.6	4.0	2.9
4-6	1 1/2	6.1	2.5	2.9	3.5	5.0	9.6	12.0	4.5	9.4	10.9	4.0	3.3
	2	6.1	2.5	2.9	3.5	5.0	9.6	12.0	4.5	9.4	11.6	5.0	4.1
	1	5.5	1.9	2.3	3.5	5.0	16.3	18.0	4.5	16.1	16.9	4.0	2.5
	1 1/4	6.1	2.5	2.9	3.5	5.0	15.7	18.0	4.5	15.4	16.6	4.0	2.9
4-12	1 1/2	6.1	2.5	2.9	3.5	5.0	15.6	18.0	4.5	15.4	16.9	4.0	3.3
	2	6.1	2.5	2.9	3.5	5.0	15.6	18.0	4.5	15.4	17.6	5.0	4.1
Dime	Dimensions are for reference only and should not be used for hard plumbing. Request a drawing from filters@rosedaleproducts.com												



Model 4 Housing Code - How to Order

CONFIGURE YOUR PART NUMBER (EXAMPLE: 4-12-1P-1-500-S-B-S-M40-D-C)

























MODEL NUMBER HOUSING SIZE PIPE SIZE OUTLET STYLE PRESSURE RATING

HOUSING MATERIAL COVER SEAL

VER BASKET AL SEAL BASKET TYPE BASKET, MEDIA SIZE DISPLACER ASME CODE STAMP

Α	MODEL NUMBER	CODE
	EYENUT COVER	4
	CLAMP COVER	LCO4

В	HOUSING SIZE	CODE
	6 INCH	6
	12 INCH	12

С	PIPE SIZE, NPT AND FLANGED ¹	CODE
	1-IN. FEMALE NPT	1P
	1-1/2-IN. FEMALE NPT	1-1/2P
	2-IN. FEMALE NPT	2P

D	OUTLET STYLE	CODE
	воттом	1
	SIDE HIGH	2
	BOTTOM ELBOW	3
	SAME SIDE HIGH	D

Е	PRESSURE RATING ¹	CODE
	200 PSI (NPT) (LCO4 ONLY)	200
	500 PSI (NPT)	500

F	HOUSING MATERIAL	CODE
	CARBON STEEL	С
	304 STAINLESS STEEL	S
	316 STAINLESS STEEL	S316

G	COVER SEAL	CODE
	BUNA N	В
	ETHYLENE PROPYLENE	E
	FLUOROELASTOMER	V
	COVER SEAL - EYENUT COVER ONLY	CODE
	FEP/PFA	TEV
	PTFE (SOLID WHITE)	TSW

Н	BASKET SEAL	CODE
	NO SEAL (WITH BAG TYPE BASKETS)	N
	SEAL REQUIRED (ON STRAINER TYPE BASKETS)	S

BASKET TYPE	CODE
FILTER BAG BASKET, 9/64 PERFORATIONS ²	РВ
STRAINER BASKET, PERFORATED METAL	Р
FILTER BAG BASKET, PERFORATED, MESH LINED ²	ВМ
STRAINER BASKET, PERFORATED, MESH LINED W/ SPRING HANDLE	М
FILTER BAG BASKET, HEAVY WIRE MESH ²	HWM

		,		
J	BASKET, MEDIA SIZE	CODE		
	NO SYMBOL FOR PB BASKET			
		PERF SIZES	MESH SIZES	
	PERFORATION DIAMETERS	1/4	20	
	(P BASKETS)	9/64	40	
		3/8	60	
	MESH SIZES (M AND BM BASKETS)		80	
	(MITHUE SIN BROKETS)		100	
			200	

K	DISPLACER	CODE
	DISPLACER	D

L	ASME CODE STAMP	CODE
	CODE STAMP - EYENUT COVER ONLY	С

- 1. Higher pressure ratings and alternative connections available. Consult factory.
- 2. Filter bags are specified separately.