

# PACSystems™ RX3i CPL410

## Edge Controller featuring PACEdge Technology

### Designed for Real-world Demands

Emerson's PACSystems RX3i CPL410 edge controller is a flexible and high-performance control system ideal for a range of applications, including water wastewater, metro, industrial steam, automotive, chemical, oil and gas, discrete manufacturing and modular machine designs. These diverse applications require a compact controller that delivers the high performance and flexibility needed to run application-specific control reliably.

The PACSystems RX3i CPL410 augments real-time deterministic control with embedded PACEdge technology, delivering near-real-time advice through market analysis, fleet and enterprise data, or asset/process knowledge to optimize business outcomes.

The CPL410 includes PACEdge with Linux and provides an open platform for reliable, secure communication and analytics using either cloud-based or edge-based apps. Controls can now be programmed to dynamically influence business outcomes, generate new forms of revenue, and improve profitability.

### Reliable, High-Speed Performance

The PACSystems RX3i CPL410 runs on a real-time operating system allowing it to deliver reliable and secure industrial applications. It offers premier high-speed performance and secure data handling for any multi-disciplined control system. A generous working memory accommodates large programs and extensive data storage. The quad-core high-speed microprocessor executes programs faster than ever before. It supports industry-standard PROFINET with I/O update rates as fast as 8ms for 16 devices. With Ethernet interface rates up to 1 Gbps, the CPL410 is built for rapid, reliable data interchange.



### Industrial Internet Enabled with PACEdge Technology

Emerson's edge controllers use realtime hypervisor technology to run realtime deterministic control applications concurrently with the PACEdge with Linux technology in a safe and cooperative manner without impacting each other. PACEdge technology is an Industrial Internet enabled coprocessor platform that enables customers to not only connect to their preferred cloud service, but also allows them to develop and run data processing Linux-based applications next to the control system to optimize their processes for better outcomes. Fleet-level analytics and access to realtime information enabled by the CPL410 is critical to OEMs and machine builders looking to get the most from their equipment fleets, minimize travel and maintenance costs, and quickly create and deploy intellectual property to differentiate their machines.

## Advanced Security

Industrial controls are constant targets of cyber threats. We understand the risk involved in securing our customers’ most important assets. We believe in defense-in-depth architectures to secure assets from potential cyber threats.

With Achilles Level 2 Certification, the RX3i CPL410 has been developed to be secure by design, incorporating technologies such as Trusted Platform Modules, and secure boot. A centralized configuration allows encrypted firmware updates to be executed from a secure central location. A broad suite of cyber-security technology and tools help prevent unauthorized updates while built-in security communication protocols help protect against man-in-the middle and denial of service attacks.

## Flexible Redundancy Tailored to Your Needs

Building on our market leadership and decades of expertise in mission critical backup power and critical cooling solutions, PACSystems High Availability with PROFINET is a flexible and intelligent high-availability control system that helps ensure maximum uptime while reducing total cost of ownership (TCO) through easier configuration, operation, and maintenance.

Built on a scalable, synchronized, hotstandby redundancy control platform, the PACSystems High Availability on CPL410 solutions provide uninterrupted control of your applications and processes with total transparency.

## Specifications

- Microprocessor – 1.2 GHz AMD G Series Quad Core
- PACSystems: Operating System - VxWorks
- PACEdge: Operating System - Linux, Ubuntu 16.04

### Temperature Range

- -40°C to 70°C

### Power Requirements

- Input Power (Max) – 20 Watts
- Input Voltage (Min) – 18 Vdc
- Input Voltage (Max) – 30 Vdc
- Memory Backup Mechanism – Energy Pack: IC695ACC403

### Firmware Upgrade

- CPU Firmware Upgrade Mechanism – Web Interface/ Ethernet Port

## Key Benefits

**Cloud Agnostic Platform.** PACEdge with Linux technology allows for secure connection to the customer’s preferred cloud, leveraging data to analyze and optimize business operations and improve profitability.

**Co-processor Engine.** A co-processor engine means that existing Linux-based applications can be quickly integrated with CPL410 to enable more intelligent controls.

**Reduced Risk.** Built on the strong foundation of 40 years’ experience providing real-time, deterministic controls for the world’s industrial assets, the CPL410 is secure by design, enabling secure operations and connectivity from edge to cloud.

**Reduced Lifecycle Cost.** Advanced capabilities simplify system architecture and reduce applied engineering costs. Costs are further reduced with embedded PROFINET, accommodating dedicated I/O for application-specific needs

**Maximum Uptime.** Our market-leading PACSystems highavailability solutions CPL410 offers a best-in-class high-availability control system for concurrent maintainability and elimination of single points of failure, maximizing uptime.

### Display

- OLED Display

### Program Portability

- RX3i PACSystems Applications using Family Type Conversion

### Program Security

- Secure Boot
- Trusted Platform Module (TPM)

### Program Storage

- PACSystems: RAM – 64 Mbytes
- PACSystems: Non-Volatile Flash – 64 Mbytes
- PACSystems: Energy Pack Capacitors, Life Expectancy – 5 years
- PACEdge: RAM – 2 GB
- PACEdge: Storage – 50 GB SSD

**Auxiliary Storage**

- PACEdge: 1x USB 3.0

**Marine\***

- ABS, DNV-GL, BV, LR

**Communications**

- LAN1 – 10/100/1000 Mbps supported by 1x unswitched RJ-45
- LAN2 - 10/100/1000 Mbps supported by 2x switched RJ-45 connectors
- LAN3 - 10/100/1000 Mbps supported by 2x switched RJ-45 connectors
- PACEdge with Linux– 10/100/1000 Mbps supported by 1x RJ-45
- USB – USB-A 3.0 x2 (Left port dedicated to PACEdge)

**Protocols**

- SRTCP
- Modbus TCP
- Ethernet Global Data (EGD)
- HART Passthrough
- PROFINET
- MRP
- OPC-UA Server with secure access
- DNP3.0 Ethernet Outstation – L3

**PACEdge Default Software Components**

- SQLite database
- OPC-UA Client
- Python script interpreter
- Apache webserver

\* Only on CPE400 versions

**EU**

- CE Mark
- EMC Directive
  - IEC/EN 61131-2: 2007 (sections 8-10, Zone B)
  - IEC/EN 61000-6-2: 2005 Ed 2.0
  - IEC/EN 61000-6-4: 2006 Ed 2.0
  - CISPR 11:2009 +A1: 2010 / EN 55011: 2009 +A1: 2010
  - CISPR 22: 2010 / EN55022: 2010/AC:2011, (Class A)
  - CISPR 24: 2010 / EN55024: 2010
  - IEC/EN 61131-2: 2007 (sections 4 & 6)
- ATEX Directive
  - Category 3 equipment - [II 3 G]
  - EN 60079-0: 2012 A+11:2013
  - EN 60079-7: 2015 [Type of Protection Ex ec]
- RoHS Directive
- REACH Regulation
- WEEE Directive

**US**

- FCC 47 CFR 15 Subpart B, Class A
- Hazardous Locations
  - ISA 12.12.01: 2015, Class I Div. 2 Groups ABCD
  - UL 60079-0 Ed 6.0 (2013), Class I, Zone 2 Gas Group ABCD
  - UL 60079-15 Edition 4.0 (2013), [Ex nA]

**Canada**

- ICES-003:2016 (Class A)
- Hazardous Locations
  - CSA C22.2 No. 213-15
  - CAN/CSA-C22.2 NO. 60079-0:15, Class I, Zone 2
  - CAN/CSA-C22.2 NO. 60079-15:12
- WEEE & Battery Regulations

**Environmental**

- IEC/EN 61131-2: 2007 (sections 5 & 6)
- Storage
  - Dry Heat - IEC 60068-2-2: 1974 test Bb (70°C @ 16hrs, unpowered)
  - Cold Temp - IEC 60068-2-1: 2007 test Ab (-40°C @ 16hrs, unpowered)
- Damp Heat
  - IEC 60068-2-30: 2005 test Db (unpowered, 55°C, 2x)
- Marine Damp Heat
  - IEC 60068-2-30: 2005 test Db (powered & unpowered, 55°C, 95%RH, 12hr x 2cycles)
- Sinusoidal Vibration
  - IEC 60068-2-6: 1995 (test Fc)
- Shock
  - IEC 60068-2-27: 1987 (test Ea)

## Ordering Information

Part Number	Description
IC695CPL410	RX3i CPL410 Standalone Edge Controller
IC695CKL410	RX3i CPL410 Standalone Edge Controller, with Energy Pack
IC695CPE400	RX3i CPE400 Standalone Edge Controller with PREDIX Connectivity
IC695CPK400	RX3i CPE400 Standalone Edge Controller with PREDIX Connectivity, with Energy Pack
IC695CPE400CA	RX3i CPE400 Standalone Edge Controller with PREDIX Connectivity, Conformal Coated

### United States Office

Emerson Automation Solutions  
Intelligent Platforms, LLC  
2500 Austin Dr  
Charlottesville, VA

### Germany Office

Emerson Automation Solutions  
ICC Intelligent Platforms  
GmbH  
Memminger Straße 14  
Augsburg, DE 86159  
T: +49 821 50340

### China Office:

Emerson Automation Solutions Intelligent  
Platforms (Shanghai) Co., Ltd  
No.1277, Xin Jin Qiao Rd, Pudong,  
Shanghai, China, 201206

### Brazil Office:

Emerson Automation Solutions  
Rua Irmã Gabriela, 51 – Cidade Monções  
São Paulo – SP, 04571-130

### Singapore Office

Emerson Automation Solutions Intelligent  
Platforms Asia Pacific Pte. Ltd.  
1 Pandan Cres,  
Singapore, 128461

### India Office

Emerson Automation Solutions  
Intelligent Platforms Pvt. Ltd.,  
Building No.8, Ground Floor Velankani Tech Park, No.43  
Electronics City Phase I, Hosur Rd  
Bangalore-560100

©2020 Emerson. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. All other marks are property of their respective owners.

The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services describe herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products an any time without notice.

